DATASHEET - Z-BB/UL18/2X1P1MU+AUX/38

Phase busbar, 2x1-phase+HS, 18qmm, pin, 1m

Part no. **Z-BB/UL18/2X1P1MU+AUX/38**
171142

General specifications			
Product name			Eaton Moeller series busbar
Part no.			Z-BB/UL18/2X1P1MU+AUX/38
EAN			4015081676316
Product Length/Depth			1001 millimetre
Product height			56.8 millimetre
Product width			19.3 millimetre
Product weight			0.787 kilogram
Compliances			RoHS conform
Product Tradename			None
Product Type			Busbar
Product Sub Type			None
Product Specification Details			
Accessory/spare part type			Busbar for miniature circuit breaker
Ambient operating temperature - max			100 °C
Ambient operating temperature - min			-5 °C
Application			Switchgear for industrial and advanced commercial applications
Color			Other
Cross section			18 mm^2
Electric connection type			Pin
Features			Can be cut to size Insulated
Functions			Busbar
Heat dissipation capacity			0 W
Heat dissipation per pole, current-dependent			0 W
Number of modular spacings			1
Number of phases			2
Number of poles			Two-pole
Pitch dimensions			26.4 mm
Rated conditional short-circuit current (Iq)			0 kA
Rated operational voltage (Ue) - max			600 V
Rated short-time withstand current (Icw)			0 kA
Rated surge voltage			10 kV
Rated uninterrupted current (Iu)			80 A
Static heat dissipation, non-current-dependent			0 W
Suitable for			Devices with auxiliary switch
Suitable for number of devices			39
Type			Z-BB/UL Busbar
Used with			Z-BB/UL Busbar

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Phase busbar (EC000215)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar (ecl@ss13-27-37-13-06 [ACN992016])

Number of phases			2
Number of poles			2
Suitable for number of devices			39
Module width		mm	26.4

Cross section		mm^2	18
Length		mm	1001
Can be cut to size			Yes
Width in number of modular spacings			1
Rated permanent current Iu		A	80
Type of electric connection			Pin
Insulated			Yes
Rated surge voltage		kV	10
Conditioned rated short-circuit current Iq		kA	0
Max. rated operation voltage Ue		V	600
Rated short-time withstand current Icw		kA	0
Suitable for devices with N-conductor			No
Suitable for devices with auxiliary switch			Yes
Colour			Other

© 04/2023 by Eaton Industries GmbH