ENDURO S3

Standard EN ISO 20345 : 2011

LEMAITRE
La Sécurité depuis 1974



Duo Protection®

Solution against the risks of perforation designed by Lemaitre for and with the construction industry.

Anti-puncture midsole: high tenacity textile «0» penetration
100% protection of the arch of the foot

Anti-puncture midsole: stainless steel
+ 80% performance compared to the textile insert

Sizes 35 to 49 Ref. **ENDUS30BFSN**

Product Highlights

- **Heavy duty boot available with men's and women's fit.**
- **Ankle protection by Lemaitre:** Malleolus protection against side impacts
- **2,0 mm thick high strengh leather** (against abrasion, tearing and puncture).
- **Tongue with outer gusset** to prevent any infiltration of dust / stones.
- **Anti-abrasion scuffcap**, increased resistance
- **Anatomical and antibacterial Energy+ insock:** impact reduction, odor neutralization.
- **Protective toe-cap**: composite HDFC.
- **Puncture-resistant midsole:** stainless steel and high tenacity fabric "0" penetration.



Semelle TRAILIUM PU2D antistatique

- **4 mm studs** suitable for construction and heavy duty industry
- **Drainage channels for liquids and mud** to avoid any risk of aquaplaning
- **Lateral edges and 15mm raised heel:** reinforced grip on ladder rungs
- **Large bearing surface,** optimal stability
- **Arch support and heel cushioning:** MSD prevention

APPLICATION

- Construction
- Outdoor activities
- Works requiring increased protection against perforation

MARQUE FRANÇAISE

ÉLABORÉ DANS LE RESPECT DE L'ANATOMIE DU PIED

lemaitre-securite.com

An exacting attitude to quality is our culture, safety our priority

ENDURO S3

An Ci SRC

Standard EN ISO 20345 : 2011

VARIANT



Adventure S3 SRC
ADVES30BFSN

Characteristics of the upper

- **Upper material:** water-repellent oiled split leather with reinforced anti-abrasion vamp
- **Tongue with outer gusset:** water-repellent leather
- **Lining:** 3D microporous fabric

Caractéristiques de la semelle

- **Designation :** TRAILIUM PU2D
- **Material:** polyurethane / polyurethane
- **Antistatic sole**
- **SRA Adhesion coefficient:**
  forward flat slip: 0,35 standard ≥ 0,32)
  forward heel slip: 0,38 (standard ≥ 0,28)
- **SRB Adhesion coefficient:**
  forward flat slip: 0,19(standard ≥ 0,18)
  forward heel slip: 0,17 (standard ≥ 0,13)

Practical information

Women fitting 35-39	**Men fitting** 40-49
Weight of one shoe size 38 : 730 g	Weight of one shoe size 42 : 810 g
CERTIFICATION N° 0075/007/161/07/19/2226 EXT 03/09/19	**CERTIFICATION N°** 0075/007/161/07/19/2226 EXT 02/09/19

Packaging

sizes 35 to 39	**sizes 40 to 49**
shoebox 345 x 230 x 122 mm	**shoebox** 355 x 340 x 130 mm
carton 660 x 450 x 360 mm	**carton** 670 x 340 x 360 mm
10 shoeboxes per carton	**5 shoeboxes per carton**

Gencods

35	3237154273357	**43**	3237154273432
36	3237154273364	**44**	3237154273449
37	3237154273371	**45**	3237154273456
38	3237154273388	**46**	3237154273463
39	3237154273395	**47**	3237154273470
40	3237154273401	**48**	3237154273487
41	3237154273418	**49**	3237154273494
42	3237154273425		

Memo for basic and additional requirements of the standard EN ISO 20345: 2011

Safety Footwear					
SBP					
S1			A	E	Fo
S1P			A	E	Fo
S2			A	E	Fo	Wru
S3			A	E	Fo	Wru

200 J toe-cap: protection of the forefoot against impact and crushing.

Anti-perforation insert 1100 N: foot protection against perforation.

- A — Anti-static footwear
- Ci — Insulation against cold
- E — Shock absorption at the heel
- Hi — Insulation against heat
- Fo — Fuel oil-resistant outsole
- Hro — Outsole resistance to hot contact
- Wru — Water penetration and water absorption resistant upper
- Wr — Water resistant
- ESD — Electrostatic discharge
- An — Ankle protection

- SRA — Slip-resistance on ceramic floors with detergent
- SRB — Slip-resistance on steel floors with glycerol
- SRC = SRA + SRB

Lemaitre Sécurité
17 rue de Bitschhoffen - CS 90024
F - 67350 Val de Moder
Tél. +33 (0)3 88 72 28 80

lemaitre-securite.com

LEMAITRE
Safety since 1974

DON_LS 04 TDS 0101
Update: 22/10/21

Member of SYNAMAP