Specifications

Eaton 127737

Catalog Number: 127737

Eaton Moeller series NZM - Molded Case Circuit Breaker. Screw connection set, 4p, for 12-20mm, cu



General specifications

Product Name
Eaton Moeller series NZM connection type

Catalog Number
127737

EAN
4015081251476

Product Length/Depth
70 mm

Product Height
60 mm

Product Width
40 mm

Product Weight
0.32 kg

Compliances
IEC
RoHS conform

Powering Business Worldwide

Product specifications

Used with

NZM4-4, N4-4

Type

Accessory Screw connection Terminal

Special features

Double hole fitting with M10 screws

Amperage Rating

1600 A

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be

Resources

Brochures

eaton-digital-nzm-brochure-br013003en-en-us.pdf

eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf

Catalogs

eaton-digital-nzm-catalog-ca013003en-en-us.pdf

Declarations of conformity

DA-DC-03_NZM4

Drawings

eaton-circuit-breaker-connection-nzm-screw-connection-dimensions.eps

Installation instructions

IL01210017Z

Installation videos

The new digital NZM Range

Introduction of the new digital circuit breaker NZM

mCAD model

DA-CS-nzm4_xks

DA-CD-nzm4_xks

Technical data sheets

eaton-nzm-technical-information-sheet

evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Frame

NZM4

Suitable for

Copper cable lugs
Four-pole

Number of poles

Four-pole

Terminal capacity (copper strip)

10 segments of 50 mm x 1 mm (2x)

Model

Other

Terminal capacity (stranded cable)

50 mm² - 185 mm² (4x)
250 - 350 AWG/kcmil (1x)
Max. 350 AWG/kcmil (4x)

120 mm² - 185 mm² (1x)

Terminal capacity (copper busbar)

50 mm x 10 mm (2x)

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia