Date: 11/04/2023

TR33, PT100-4w, cl.A, G1/2 fixed, 150 mm x 6 mm

TR33 Miniature resistance thermometer, thread-mounted

Item number:	48796876
Quantity:	1 pcs.
Order code:	TR33-Z-P4-ZIZZZZ-1360150-070-7ZZ-ZZZ R33 0220ZPZZZZWIKA0Z
Overview:	TR33, PT100-4w, cl.A, G1/2 fixed, 150 mm x 6 mm Output signal: PT100-4w, cl.A Electrical connection: Circular connector, M12x1 Process connection: Fixed threaded hex bushing G1/2 B Process temperature: -30 ... +250°C Sensor diameter ød: 6 mm Insertion length A: 150 mm Neck length N(MH): 70 mm Permissible ambient temperature: -50 ... +85 °C (-58 ... +185 °F) Pin assignment: Standard pin connection Pt-Sensors (see datasheet) Specifications according to data sheet: TE 60.33
Details:	TR33 Miniature resistance thermometer, thread-mounted Specifications according to data sheet: TE 60.33 Electrical connection: Circular connector, M12x1 Output signal: Pt100 Class A (IEC 60751), 4-wire Process temperature: -30 ... +250°C Process connection: Fixed threaded hex bushing G1/2 B Sensor diameter ød: 6 mm Insertion length A: 150 mm Neck length N(MH): 70 mm Permissible ambient temperature: -50 ... +85 °C (-58 ... +185 °F) Pin assignment: Standard pin connection Pt-Sensors (see datasheet)

© 2023 - WIKA Instruments s.a.r.l.