PRODUCT-DETAILS

# OS32GD12

## OS32GD12 SWITCH FUSE



### General Information

| | |
|---|---|
| Extended Product Type | OS32GD12 |
| Product ID | 1SCA115199R1001 |
| EAN | 6417019476391 |
| Catalog Description | OS32GD12 SWITCH FUSE |
| Long Description | Switch-disconnector fuse, 32A, 3-pole, DIN 000, front operated. |

### ABB EcoSolutions

| | |
|---|---|
| ABB Site Meeting Group Waste To Landfill Target | UL 2799 Zero Waste To Landfill Validation available |
| End Of Life Disassembling Instructions | 1SCC311048M0201 |
| Environmental Product Declaration - EPD | 1SCC311195D0201 |

### Material Compliance

© 2025 ABB. All rights reserved.

| | |
|---|---|
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658 |
| REACH Declaration | 1SCC011021D0201 |
| RoHS Declaration | 1SCC011020D0201 |
| RoHS Information | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| Toxic Substances Control Act - TSCA | 1SCC011025D0201 |

## Popular Downloads

| | |
|---|---|
| Data Sheet, Technical Information | 1SCC311013C0201 |
| Instructions and Manuals | 1SCC311036M0212 |
| Mechanical Drawings | OS63GD12.igs |
| Environmental Product Declaration - EPD | 1SCC311195D0201 |

## Environmental

| | |
|---|---|
| Degree of Protection | acc. to IEC 60529 IP20 |
| Pollution Degree | 3 |

## Ordering

| | |
|---|---|
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85365080 |
| Country or Territory of Origin | Finland |

## Dimensions

| | |
|---|---|
| Product Net Width | 138 mm |
| Product Net Height | 112 mm |
| Product Net Depth / Length | 121 mm |
| Product Net Weight | 0.99 kg<br>2.18 lb |

## Container Information

| | |
|---|---|
| Package Level 1 Units | box 1 piece |
| Package Level 1 Width | 170 mm<br>6.7 in |
| Package Level 1 Depth / Length | 190 mm<br>7.5 in |
| Package Level 1 Height | 145 mm<br>5.7 in |
| Package Level 1 Gross Weight | 1.1 kg<br>2.5 lb |
| Package Level 1 EAN | 6417019476391 |

© 2025 ABB. All rights reserved.

## Technical

| | |
|---|---|
| Cable Cross-Section | 2.5 ... 25 mm² |
| Connecting Capacity | Stranded 2.5 … 25 mm²<br>Flexible 2.5 … 25 mm² |
| Conventional Free-air Thermal Current ($I_{th}$) | Θ = 40 °C 32 A |
| Conventional Thermal Current ($I_{the}$) | Fully Enclosed 32 A |
| Degree of Protection | acc. to IEC 60529 IP20 |
| Fuse Size | NH000 |
| Fuse System | DIN |
| Handle Type | Handle not included |
| Mounting Type | Base mounting |
| Number of Poles | 3P |
| Operating Mode | Front |
| Pollution Degree | 3 |
| Position of Line Terminals | Top In - Bottom Out, Bottom In - Top Out |
| Power Loss | at Rated Operating Conditions per Pole 1 W |
| Rated Conditional Short-Circuit Current ($I_{nc}$) | (500 V) 100 kA<br>(690 V) 80 kA |
| Rated Current ($I_n$) | Main Circuit 32 A |
| Rated Impulse Withstand Voltage ($U_{imp}$) | 12 kV |
| Rated Insulation Voltage ($U_i$) | 1000 V |
| Rated Operational Current AC-21A ($I_e$) | (500 V) 32 A<br>(690 V) 32 A |
| Rated Operational Current AC-22A ($I_e$) | (500 V) 32 A<br>(690 V) 32 A |
| Rated Operational Current AC-23A ($I_e$) | (500 V) 32 A<br>(690 V) 32 A |
| Rated Operational Power AC-23A ($P_e$) | (220 ... 240 V) 7.5 kW<br>(400 V) 15 kW<br>(415 V) 15 kW<br>(500 V) 18.5 kW<br>(690 V) 22 kW |
| Rated Operational Voltage | Main Circuit 690 V AC |
| Rated Short-time Withstand Current Low Voltage ($I_{cw}$) | for 1 s 2.5 kiloampere rms |
| Recommended Screw Driver | Main Circuit Hexagon 4 |
| Standards | IEC 60947-3 |
| Switches Operating Mechanism | 12 (Between the Poles) |
| Terminal Type | Screw Terminals |
| Tightening Torque | 3 N·m<br>4 N·m |
| Wire Stripping Length | Main Circuit 12 mm<br>Main Circuit 0.47 in |

## Technical UL/CSA

| | |
|---|---|
| Wire Stripping Length | Main Circuit 12 mm<br>Main Circuit 0.47 in |

© 2025 ABB. All rights reserved.

| | |
|---|---|
| Recommended Screw Driver | Main Circuit Hexagon 4 |
| Tightening Torque | 3 N·m<br>4 N·m |

## Certificates and Declarations

| | |
|---|---|
| A2L Certificate – IEC | 1SCC311208D0201 |
| ATEX Certificate | No certification needed |
| CCC Certificate | CCC OS32-63G_ 2016.pdf |
| Declaration of Conformity - CE | 1SCC311136D2703 |
| DNV GL Certificate | 1SCC311125D0203 |
| UL Certificate | No certification needed |

## External Classifications and Standards

| | |
|---|---|
| Object Classification Code | Q |
| ETIM 9 | EC001040 - Fuse switch disconnector |
| ETIM 10 | EC001040 - Fuse switch disconnector |
| UNSPSC | 39122233 |
| IDEA Granular Category Code (IGCC) | 5291 >> Fuse switch disconnector |
| eClass | V11.1 : 27371401 |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |
| E-Number (Finland) | 3660322 |

## Categories

Low Voltage Products and Systems → Switches → Switch Fuses



© 2025 ABB. All rights reserved.