Specifications

Eaton 293968



Catalog Number: 293968

Eaton Moeller® series DILK Contactor for capacitors, with series resistors, 12.5 kVAr, 48 V 50 Hz

General specifications

Product Name
Eaton Moeller® series DILK capacity contactor

Catalog Number
293968

EAN
4015082939687

Product Length/Depth
138 mm

Product Height
135 mm

Product Width
45 mm

Product Weight
0.51 kg

Certifications
CSA
CSA Class No.: 3211-04
UL
IEC/EN 60947
CSA File No.: 012528
UL 60947-4-1
CE
UL File No.: E29096
CSA-C22.2 No. 60947-4-1-14
IEC/EN 60947-4-1
UL Category Control No.: NLDX

Powering Business Worldwide

Features Functions

Fitted with:

Series resistors

General

Application

Contactors for power factor correction

Degree of protection

IP00

Lifespan, electrical

150,000 Operations

Connection

Screw terminals

Operating frequency

120 Operations/h

Product category

DILK Contactors for capacitors

Protection

Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)

Voltage type

AC

Climatic environmental conditions

Ambient operating temperature - min

-25 °C

Ambient operating temperature - max

60 °C

Ambient operating temperature (enclosed) - min

25 °C

Ambient operating temperature (enclosed) - max

40 °C

Electro magnetic compatibility

Emitted interference

According to EN 60947-1

Interference immunity

According to EN 60947-1

Terminal capacities

Terminal capacity (flexible with ferrule)

1 x (0.75 - 16) mm², Main cables

Terminal capacity (solid)

1 x (0.75 - 16) mm², Main cables

Terminal capacity (solid/stranded AWG)

18 - 6, Main cables

Terminal capacity (stranded)

1 x 16 mm², Main cables

Electrical rating

Rated operational current (Ie)

18 A at 230 V (three-phase capacitors, open)
18 A at 525 V (three-phase capacitors, open)
18 A at 690 V (three-phase capacitors, open)
16 A at 690 V (three-phase capacitors, enclosed)
16 A at 400 V (three-phase capacitors, enclosed)
16 A at 525 V (three-phase capacitors, enclosed)
18 A at 400 V (three-phase capacitors, open)
16 A at 230 V (three-phase capacitors, enclosed)

Rated operational power at AC-6B, 220/230 V, 50 Hz

7.5 kW

Rated operational power at AC-6B, 380/400 V, 50 Hz

12.5 kW

Rated operational power at AC-6B, 525 V, 50 Hz

16.7 kW

Rated operational power at AC-6B, 690 V, 50 Hz

20 kW

Switching capacity

Switching capacity (auxiliary contacts, general use)

10 A, 600 V AC, (UL/CSA)
1 A, 250 V DC, (UL/CSA)

Switching capacity (auxiliary contacts, pilot duty)

A600, AC operated (UL/CSA)
P300, DC operated (UL/CSA)

Magnet system

Arcing time

10 ms

Drop-out voltage

AC operated: 0.6 - 0.3 x UC, AC operated

Duty factor

100 %

Pick-up voltage

0.8 - 1.1 V AC x Uc

Power consumption, pick-up, 50 Hz

58 VA, Dual-frequency coil in a cold state and 1.0 x Us, at 50 Hz

Power consumption, pick-up, 60 Hz

71 VA, Dual-frequency coil in a cold state and 1.0 x Us, at 60 Hz

Power consumption, sealing, 50 Hz

2.1 W, Dual-frequency coil in a cold state and 1.0 x Us, at 50 Hz
7.6 VA, Dual-frequency coil in a cold state and 1.0 x Us, at 50 Hz

Power consumption, sealing, 60 Hz

9.3 VA, Dual-frequency coil in a cold state and 1.0 x Us, at 60 Hz

2.1 W, Dual-frequency coil in a cold state and 1.0 x Us, at 60 Hz

Rated control supply voltage (Us) at AC, 50 Hz - min

48 V

Rated control supply voltage (Us) at AC, 50 Hz - max

48 V

Rated control supply voltage (Us) at AC, 60 Hz - min

0 V

Rated control supply voltage (Us) at AC, 60 Hz - max

0 V

Rated control supply voltage (Us) at DC - min

0 V

Rated control supply voltage (Us) at DC - max

0 V

Switching time (AC operated, make contacts, closing delay) - min

16 ms

Switching time (AC operated, make contacts, closing delay) - max

22 ms

Switching time (AC operated, make contacts, opening delay) - min

8 ms

Switching time (AC operated, make contacts, opening delay) - max

14 ms

Contacts

Making capacity without damping (I-peak value)

180 x Ie

Number of auxiliary contacts (normally closed contacts)

1

Number of auxiliary contacts (normally open contacts)

1

Special purpose ratings

Special purpose rating of capacitor switching

18 A, 240 V 60 Hz 3phase, (UL/CSA)
15 kVar, 480 V 60 Hz 3phase, (UL/CSA)
18 A, 480 V 60 Hz 3phase, (UL/CSA)
7.5 kVar, 240 V 60 Hz 3phase, (UL/CSA)
14.4 A, 600 V 60 Hz 3phase, (UL/CSA)
15 kVar, 600 V 60 Hz 3phase, (UL/CSA)

Design verification

Equipment heat dissipation, current-dependent Pvid

2.1 W

Heat dissipation capacity Pdiss

0 W

Heat dissipation per pole, current-dependent Pvid

0.7 W

Rated operational current for specified heat dissipation (In)

18 A

Static heat dissipation, non-current-dependent Pvs

2.1 W

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Resources

Catalogs

eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf

Product Range Catalog Switching and protecting motors

SmartWire-DT Catalog

Declarations of conformity

DA-DC-00004814.pdf

DA-DC-00004785.pdf

Drawings

eaton-contactors-dilk-dimensions-002.eps

eaton-contactors-mounting-dilm-dimensions.eps

eaton-contactors-mounting-dilm-dimensions-002.eps

eaton-contactors-dilk-dimensions.eps

eaton-contactors-dilk-dimensions-004.eps

eaton-contactors-dilk-3d-drawing.eps

eCAD model

ETN.DILK12-11(48V50HZ).edz

Installation instructions

IL03407038Z

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

Installation videos

WIN-WIN with push-in technology

mCAD model

eaton-dilk12-25-3d-model.stp

DA-CS-dil_m17_38

DA-CD-dil_m17_38

eaton-dilk12-25-drawing.dwg

Wiring diagrams

eaton-contactors-circuit-dilk-wiring-diagram-002.eps

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia