Date: 24/01/2024

pressure gauge with mounted diaphragm seals, with threaded connection

pressure gauge with mounted diaphragm seals, with threaded connection

Item number:	14200500
Quantity:	1 pcs.
Order code:	DSS34M-F2BG416-DA1C5465-G2MD8C1-Z ZZ 2HZZ003016E
Overview:	pressure gauge with mounted diaphragm seals, with threaded connection Typ: DSS34M Manometer according to EN 837-1 nominal size 100 mm 0...16 bar lower mount Measuring system class 1.0 laminated safety glass Pressure Gauge Standard direct assembly System fill fluid: KN 2 Silicone oil for general applications Process temperature min.: - 10°C Process temperature max.: + 150°C Ambient temperature pressure meas. min: + 10°C Ambient temperature pressure meas. max: + 40°C threaded connection, welded design following BSPP (e.g. G 1/2) G 1/2" male PN 160 Wetted parts: 316L Temperature error prozess in mbar/10°K: 3 mbar Temperature error ambient in mbar/10°K: 16 mbar
Details:	pressure gauge with mounted diaphragm seals, with threaded connection Model: DSS34M Specifications according to data sheet: DS 95.15 Pressure measuring instrument: Manometer according to EN 837-1 nominal size 100 mm Case filling: without Unit of outer Scale: bar Scale range: 0...16 bar Assembly: direct assembly System fill fluid: KN 2 Silicone oil for general applications

© 2024 - WIKA Instruments s.a.r.l.

Unit of temperature: Celsius
Process temperature min.: - 10°C
Process temperature max.: + 150°C
Ambient temperature pressure meas. min: + 10°C
Ambient temperature pressure meas. max: + 40°C
Process connection standard: following BSPP (e.g. G 1/2)
Threaded connection: G 1/2" male
Nominal pressure rating: PN 160
Wetted parts: Stainless steel 1.4404/1.4435 (316L); UNS S31603

© 2024 - WIKA Instruments s.a.r.l.