DATASHEET - TSDW1COMIN

Series connection digital time switch 1 channel, 7 days, text line, 1 TLE

Part no.	**TSDW1COMIN**
	167383
EL Number (Norway)	**1456985**

General specifications

Product name	Eaton Distribution parts
Part no.	TSDW1COMIN
EAN	4015081639199
Product Length/Depth	65.5 millimetre
Product height	90 millimetre
Product width	17.5 millimetre
Product weight	0.08 kilogram
Compliances	RoHS conform
Product Tradename	None
Product Type	Distribution parts
Product Sub Type	None
Public Consumption	Yes
Product Family Description	ES-PMCC-PDC-Eaton Distribution parts
Globally Marketable	Yes

Product Specification Details

Accuracy per day	1 s
Ambient operating temperature - max	55 °C
Ambient operating temperature - min	-25 °C
Autonomy in hours	0 h
Autonomy in years	10 a
Contact type	Change-over contact (NO/NC)
Degree of protection	IP20
EL number	1456985
Equipment heat dissipation, current-dependent	0 W
Features	Text guidance in display
Frequency supply voltage - max	60 Hz
Frequency supply voltage - min	50 Hz
Functions	Manual operation Automatic switching summer-/winter time 24 h program Holiday program Quartz controlled External programming Switching preselection Potential free switch contact 60 min. program Weekly program Hour meter
Heat dissipation capacity	0 W
Heat dissipation per pole, current-dependent	0 W
Nominal switching current at 250 V AC	16 A
Number of channels	1
Number of contacts	1
Number of memory locations	84
Output signal	Other
Rated operational current for specified heat dissipation (In)	0 A
Shortest switching time at channel 1	1 min
Shortest switching time at channel 2	0 min
Static heat dissipation, non-current-dependent	0.4 W
Supply voltage - max	240 V
Supply voltage - min	230 V

Switching power LED - max			600 W
Voltage type			AC
Width in number of modular spacings			1

Technical data ETIM 9.0

Devices for distribution board-/surface mounting (EG000062) / Digital time switch for distribution board (EC002305)

Electric engineering, automation, process control engineering / Measurement technology, process measurement technology / Measuring appliance, time / Digital time switch (ecl@ss13-27-20-01-10 [ACN653016])

Mounting method			DIN rail
Number of channels			1
Supply voltage		V	230 - 240
Voltage type (supply voltage)			AC
Frequency supply voltage		Hz	50 - 60
Autonomy in hours			0
Autonomy in years			10
Accuracy per day		s	1
Text guidance in display			Yes
External programming			Yes
With memory card			No
60 min program			Yes
24 h program			Yes
Weekly program			Yes
Annual program			No
Holiday program			Yes
Impulse program			No
Cycle program			No
Astro program			No
Random program			No
Hour meter			Yes
Mains synchronous			No
Quartz controlled			Yes
Radio-controlled			No
Radio-controlled (DCF77)			No
GPS (global positioning system)			No
Contact type			Change-over contact (NO/NC)
Number of contacts			1
Output signal			Other
Shortest switching time channel 1		min	1
Shortest switching time channel 2		min	0
Number of memory locations			84
Automatic switching summer-/winter time			Yes
Suitable for manual operation			Yes
External pushbutton input			No
Switching preselection			Yes
Nominal switching current at 250 V AC		A	16
Max. switching power LED		W	600
Potential free switch contact			Yes
Degree of protection (IP)			IP20
Width in number of modular spacings			1
Width		mm	17.5
Height		mm	90
Depth		mm	65.5

© 04/2023 by Eaton Industries GmbH