Specifications

Eaton 9702-6103-00P

Catalog Number: 9702-6103-00P

Eaton DG1 Variable frequency drive, 400 V AC, 3-phase, 205 A, 110 kW, IP54/NEMA12, DC link choke



General specifications

Product Name
Eaton DG1 variable frequency drive

Catalog Number
9702-6103-00P

EAN
4015081798285

Product Length/Depth
371 mm

Product Height
1035 mm

Product Width
486 mm

Product Weight
113.5 kg

Certifications
UL report applies to both US and Canada
CE
UL508
CSA-C22.2 No. 274-13
UL File No.: E134360
CUL
IEC/EN61800-3
UL
RoHS, ISO 9001
Specification for general requirements: IEC/EN 61800-2
C-Tick
Safety requirements: IEC/EN 61800-5
Certified by UL for use in Canada
IEC/EN 61800-3
EAC
UkrSEPRO
UL Category Control No.: NMMS, NMMS7
IEC/EN61800-5

Powering Business Worldwide

Features & Functions

Features

Externally accessible fan

Temperature-controlled fan

Parameterization: Fieldbus

Parameterization: Keypad

Parameterization: Power Xpert inControl

General

Air volume capacity

679 m³/h

Cable length

C2 ≤ 10 m, Radio interference level, maximum motor cable length

C3 ≤ 50 m, Radio interference level, maximum motor cable length

200 m, screened, maximum permissible, Motor feeder

Degree of protection

NEMA 12

IP54

Electromagnetic compatibility

1st and 2nd environments (according to EN 61800-3)

Environmental class

3C2, 3S2 (Air quality)

Fitted with:

Internal DC link

Additional PCB protection

PC connection

IGBT inverter

DC link choke

Multi-line graphic display

Radio interference suppression filter

Control unit

Frame size

FS6

Mounting position

Vertical

Number of slots

2 (expansion)

Overvoltage category

III

Pollution degree

2

Product Category

Variable frequency drives

Protection

Finger and back-of-hand proof, Protection against direct contact

(BGV A3, VBG4)

Radio interference class

C1: with external filter, for conducted emissions only
Optional external radio interference suppression filter for longer motor cable lengths and for use in different EMC environments
C2, C3: depending on the motor cable length, the connected load, and ambient conditions. External radio interference suppression filters (optional) may be necessary.

Safety function/level

STO (Safe Torque Off, SIL1, PLc Cat 1)

Shock resistance

UPS drop test (for weights inside the UPS frame)
Mechanical, According to EN 61800-5-1, IEC/EN 60068-2-27
Storage and transportation: maximum 15 g, 11 ms (inside the packaging)

Suitable for

Branch circuits, (UL/CSA)

Vibration

Resistance: 5 - 15.8 Hz, Amplitude 1 mm (peak)
Resistance: 5 - 150 Hz, According to EN 61800-5-1, IEC/EN 60068-2-6
Resistance: 15.8 – 150 Hz, 1 g, Maximum acceleration amplitude

Climatic environmental conditions

Altitude

Max. 2000 m for Corner Grounded TN Systems
Max. 3000 m
Above 1000 m with 1 % derating per 100 m
Max. 1000 m

Ambient operating temperature - min

-10 °C

Ambient operating temperature - max

50 °C

Ambient operating temperature at 150% overload - min

-30 °C

Ambient operating temperature at 150% overload - max

50 °C

Ambient storage temperature - min

-40 °C

Ambient storage temperature - max

70 °C

Climatic proofing

< 95 average relative humidity (RH), no condensation, no corrosion

Main circuit

Current limitation

0.1 - 2 x IH (CT), motor, main circuit

Efficiency

97.9 % (η)

Heat dissipation at current/speed

1164 W at 100% current and 50% speed
1361 W at 50% current and 50% speed
1463 W at 50% current and 90% speed
2105 W at 100% current and 0% speed
2480 W at 50% current and 0% speed
2767 W at 100% current and 90% speed
878 W at 25% current and 0% speed
986 W at 25% current and 50% speed

Input current ILN at 110% overload

250 A

Motor rating

Assigned motor current IM at 400 V, 50 Hz, 110% overload

234 A

Assigned motor current IM at 400 V, 50 Hz, 150% overload

196 A

Assigned motor current IM at 440 - 480 V, 60 Hz, 150% overload

180 A

Assigned motor current IM at 440/480 V, 60 Hz, 110% overload

240 A

Assigned motor current IM at 500 V, 50 Hz, 110% overload

224 A

Assigned motor current IM at 500 V, 50 Hz, 150% overload

184 A

Assigned motor power at 460/480 V, 60 Hz, 3-phase

150 HP

Input current ILN at 150% overload

189 A

Leakage current at ground IPE - max

9.5 mA

Mains current distortion

29 %

Mains switch-on frequency

Maximum of one time every 60 seconds

Mains voltage - min

380 V

Mains voltage - max

500 V

Operating mode

Sensorless vector control (SLV)
Torque regulation
U/f control
Speed control with slip compensation

Output frequency - min

0 Hz

Output frequency - max

400 Hz

Output voltage (U2)

500 V AC, 3-phase
480 V AC, 3-phase
400 V AC, 3-phase

Overload current IL at 110% overload

287.1 A

Overload current IL at 150% overload

307.5 A

Rated conditional short-circuit current (Iq)

100 kA

Rated control supply voltage

10 V DC (Us, max. 10 mA)

Rated frequency - min

45 Hz

Rated frequency - max

66 Hz

Rated operational current (Ie) at 110% overload

Assigned motor power at 460/480 V, 60 Hz, 3-phase, 110 % overload

200 HP

Apparent power

Apparent power at 400 V

180.8 kVA

Apparent power at 480 V

226 kVA

Braking function

Braking resistance

3.3 Ω

Braking torque

Adjustable to 150 % (I/Ie), DC - Main circuit
Max. 30 % MN, Standard - Main circuit
Max. 100 % of rated operational current Ie with external braking resistor - Main circuit
Adjustable to 150 %, DC - Main circuit

Switch-on threshold for the braking transistor

850 VDC

Control circuit

Number of inputs (analog)

2

Number of inputs (digital)

8

Number of outputs (analog)

2

Number of outputs (digital)

1

Number of relay outputs

3 (parameterizable, 2 changeover contacts and 1 N/O, 6 A (240 V AC) / 6 A (24 V DC))

Rated control voltage (Uc)

24 V DC (external, max. 250 mA options incl.)

261 A

Rated operational current (Ie) at 150% overload

205 A

Rated operational power at 380/400 V, 50 Hz, 3-phase

110 kW

Rated operational power at 380/400 V, 50 Hz, 3-phase, 110% overload

132 kW

Rated operational power at 500 V, 50 Hz, 3-phase

132 kW

Rated operational power at 500 V, 50 Hz, 3-phase, 110% overload

160 kW

Rated operational voltage

480 V AC, 3-phase

500 V AC, 3-phase

400 V AC, 3-phase

Resolution

0.01 Hz (Frequency resolution, setpoint value)

Short-circuit protection rating

400 A, UL (Class CC or J), Safety device (fuse or miniature circuit-breaker), Power Wiring

Starting current - max

200 %, IH, max. starting current (High Overload), For 2 seconds every 20 seconds, Power section

Supply frequency

50/60 Hz

Switching frequency

2 kHz, 1 - 10 kHz adjustable, fPWM, Power section, Main circuit

System configuration type

TN-S, TN-C, TN-C-S, TT, IT

Voltage rating - max

500 VAC

Communication

Communication interface

Modbus RTU, built in

SmartWire-DT, optional

Ethernet IP, built in

Modbus TCP, built in

BACnet MS/TP, built in

CANopen®, optional

PROFIBUS, optional

DeviceNet, optional

Connection to SmartWire-DT

In conjunction with DXG-NET-SWD SmartWire DT module

Yes

Protocol

DeviceNet

MODBUS

TCP/IP

CAN

BACnet

Other bus systems

PROFINET IO

PROFIBUS

EtherNet/IP

Design verification

Equipment heat dissipation, current-dependent Pvid

2620 W

Rated operational current for specified heat dissipation (In)

205 A

Static heat dissipation, non-current-dependent Pvs

62.45 W

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

Resources

Application notes

Torque control

Starting, stopping and operation

Electromagnetic compatibility (EMC)

PID controller

DG1 in pump and fan applications

Digital I/Os

Operating at low temperatures

Motor data and V/f curves

Dual Rating What exactly does that mean?

Connecting drives to generator supplies

Real time clock and use of the timers

Load balancing in multi motor applications

Analog I/Os

Smoke Mode and fire mode

Catalogs

Product Range Catalog Drives Engineering

Declarations of conformity

DA-DC-00004676

DA-DC-00004620.pdf

eCAD model

DA-CE-ETN.DG1-34205FN-C54C

Manuals and user guides

MN040002_EN

mCAD model

DA-CD-dg1_fs6_ohne

DA-CS-icpd_dg1_fr6_ohne

Multimedia

PowerXL DG1 Variable Frequency Drive - Setup via WebUI

Power XL General Purpose Drives

Product notifications

eaton-drives-ecodesign-directive-mz040046en-en.pdf

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia