ENGLISH

Datasheet

Stock No: 137-3393

RS Pro Black Heat Shrink Tubing, 6mm, 2:1, 100m Length



Image representative of range

Product Details

Soft PVC shrink tubes

Soft PVC shrink tubes

Shrink in both thickness (diameter) and length, in contrast to Radiflex and Polyolefine do not shrink in length.
Hot air guns can be used as a heat source.
NB: Before shrinking the tube is sensitive to temperature, and should be stored in a cool place (less than +15 °C and not in direct sunlight).
Resistant to most chemicals.
Delivered as 100 m rolls
The tube is delivered "pumped up" with air to improve shelf-life

ENGLISH

Halogen Free & Flame Retardant

New harmonised colours available in all sizes to support IEE regulations on new phase colours to BS 7671

- Flexible polyolefin tubing available in selection of colours
- Very low smoke and low toxic fume emission
- Very high flame temperature index, over 350°C
- High oxygen index, over 36%
- Ideal for use in insulating cable protectors, encapsulation of cable connectors
- Applications in all smoke sensitive areas such as public buildings, public transport, power plant, hospitals airports, submarines and underground

Specifications

Sleeve Diameter	6mm
Shrunk Diameter	3mm
Colour	Black
Sleeve Type	Heat Shrink
Shrink Ratio	2:1
Sleeve Length	100m
Material	PVC
Minimum Operating Temperature	-20°C
Maximum Operating Temperature	+90°C
Dielectric Strength	20kV/mm