TECHNICAL SPECIFICATION

RESPIRATORY PROTECTION

F600 SERIES

F621 - FFP2 - VERTICAL FOLD FLAT DISPOSABLE DUST MASK

Product Code: BGV120-000-Q00 / BGV120-000-T00



Description

Vertical fold flat respirator with foam padded adjustable nose clip

Options

Box of 40 code: BGV120-000-Q00

Box of 15 x2 pack masks retail code: BGV120-000-T00

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.
Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com
Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com.
Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

FEATURES



FOLDS FLAT
Fold flat design is compact and easy to carry in a pocket



FOAM PADDED NOSE BRIDGE, A mouldable nose bridge and foam pad on the inside for comfort and a firmer fit



TOGGLE STRAPS,
Metal free,
toggle adjustable straps create a firm and adaptable fit

COMPATIBLE PRODUCTS

EVO® Gas Goggle
EVO® Goggle Double Lens
EVO® Goggle Single Lens
Sonis® Compact Ear Defenders
Sonis®1 Ear Defenders
Sonis®2 Ear Defenders
Sonis®3 Ear Defenders
Stealth ™ 16G
Stealth ™ 7000
Stealth ™ 8000
Stealth ™ 9000
Stealth ™ Coverlite™ Overspec
Thermex™ Double Lens Goggle

SAFETY STANDARDS

EN 149:2001 + A1:2009

CERTIFICATION

CE 0370-4691-PPE/B issued by APPLUS

SPECIFICATIONS

Classification
FFP2 (Filtering Facepiece Particulate)

Filter Type
P (Protects Against Solid and Liquid Aerosols)

Usage
NR (Non-Reusable)

Activated Carbon Layer
No

Minimum Filtration Efficiency
94% For FFP2 Rated

Maximum Total Inward Leakage (TIL)
8%

Nominal Protection Factor (NPF)
12

UK Assigned Protection Factor (APF)
10

Mask Design
Vertical Fold Flat

Exhalation Valve
No

Toggle Adjustment Straps
Yes

Nose Bridge
Moulded in mask

Mask Material
Polypropylene

Filter Shelf Life
5 Years

Product Weight
16g (Approx)

ACCESSORIES

Portacount/AccuFIT Quantitive/Qualitative Face Fit Testing Kit & Spares

APPLICATIONS

- Mining, Aggregates and Quarrying
- Agriculture
- Forestry & Landscaping
- Manufacturing
- Constuction & Infrastructure
- Scaffolding & Roofing
- Welding (mild)

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.
Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com
Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com.
Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

INSTRUCTIONS FOR USE

- Mask must be fitted in accordance with the instructions supplied
- Care must be taken to ensure that the correct mask type is selected for the work to be carried out
- If in doubt as to the type of mask required, seek professional guidance

CLEANING & MAINTENANCE

- Not Applicable - Disposable Product
- Store the masks out of sunlight away from chemicals in a dry atmosphere

DIMENSIONS OF MASK

- Depth: 12.5cm / Width: 15cm

DIMENSIONS OF BOX

- Depth: 13cm / Width: 13cm / Height: 21cm

DIMENSIONS OF OUTER PACKAGING

- Quantity: 1,200 (30 inner packs of 40 masks)
- Quantity: 450 (30 inner packs of 15 x 2 masks, retail packs)
- Depth: 670mm / Width: 410mm / Height: 440mm

LIMITATIONS OF USE

- Protection will only be offered if the mask is fitted correctly
- The mask, when in contact with the skin may cause allergic
- Do not use where exposure to chemical gases may be experienced
- Use in well ventilated areas only, which are not deficient in oxygen and do not contain explosive atmospheres
- Ensure good seal around the face is created before entering the hazard area
- The working life of the mask is nominally one day (this is based on a working day shift of 8 hours), however it may be affected by many factors, including work rate, airflow and concentration of any contaminant in the atmosphere. The mask should be changed immediately if,
  a.) Breathing difficulties due to clogging are experienced,
  b.) Breakthrough of a contaminant is detected by smell, taste or any other means, or
  c.) The mask becomes damaged

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.
Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com
Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com.
Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.