PIT es Set10u-5ns basic 400463



PITestop active, set consisting of E-STOP pushbutton can be activated/ deactivated with flashing function, without logo and without E-STOP symbol, with contact block with dropout protection in accordance with EN 60947-5-1 and EN 60947-5-5 and with LED safety module PCB in the surface mount housing with M12/5-pin connection - PDP67 8DI ION PIN assignment, 2 N/C (2 N/C) in quick-connection technology.

Technical details

General data	
Approval:	CE, UKCA
Lamp:	LED
Lamp colour:	yellow, red
Technical data	
Electrical data	
Rated operating voltage:	24 V DC
Emergency stop	
Release type emergency stop:	Turn release
Switch cap. E-STOP to standard:	EN 60947-5-1
Contact fuse protection E-Stop:	≤ 1 A
Contact material E-STOP:	AgNi
Environmental data	
Ambient temperature:	-25 - 55 °C
Vibration to standard ...:	EN 60947-5-5
Peak amplitude:	Max. 0.35 mm
Clearance & creepage dist. to:	EN 60947-5-1
Overvoltage category:	II
Pollution degree clear.&creep.:	2
Mechanical data	

Mounting position:	any
Connection terminal:	M12
Height dimension:	103.2 mm
Width dimension:	72 mm
Depth dimension:	91.8 mm
Net weight:	207 g
Gross weight:	271 g
Environment	
RoHS directive:	2011/65/EU, 2015/863/EU
RoHS conformity:	yes
RoHS exceptions:	yes
RoHS except.s acc. to direct.:	6c
REACh compliance:	contains min. 1 SVHC-substance
REACh included substances:	Lead
%-part of the pollutant:	> 0,1
CAS No.:	7439-92-1
WEEE classifikation (08/2018):	5 devices (feed size < 50cm)
SCIP entry available:	0
Commercial data	
Harmonized System Code:	85371098
UNSPSC 25:	46171620
EAN-Code:	4046548094701
ECLASS version:	ECLASS-13
ECLASS Reference Feature:	27371244
ETIM Version:	ETIM-9.0
ETIM Reference Group:	EG000017
ETIM Reference Feature:	EC002034
Volume:	0 dm3