60mm Compact fan




- With electronic protection against reverse polarity. The fan only operates when the polarity is correct. Impedance-protected against locked rotor and overloading.
- Fan of fibreglass reinforced plastic. PBT housing, PA impeller
- Air exhaust over struts. Rotational direction CCW looking at rotor
- Fitted with 3 pin molex connector (22-01-2035)
- Sensor signal for speed monitoring

Part Number	Air flow @ free air m^3/h	Air flow @ free air CFM	Nominal voltage VDC	Voltage Range VDC	Noise dB(A)	Sintec-sleeve Bearings	Power input W	Nominal speed RPM	Temperature range °C	Service life L^{10} @20°C/ at 60°C Hours	Dimension A mm	Dimension B mm
612F/2L-640	15	8.8	12	10.8…13.2	11	Yes	0.28	2250	-20...+85	50,000/20,000	15	308
612F/2-638	27	15.9	12	10.8…13.2	27	Yes	1.0	3900	-20...+75	50,000/20,000	15	308
612N/2GML-096	23	13.5	12	8…15	19	Yes	0.9	3000	-20...+70	80,000/50,000	25	318

subject to alterations

Dimensions



ebm-papst UK Ltd, Chelmsford Business Park, Chelmsford, CM2 5EZ
01245 468555 sales@uk.ebmpapst.com www.ebmpapst.co.uk

ebmpapst