Date: 12/04/2023

P-30 ; 0...1.6 bar abs; 4...20 mA, 2-W

Pressure sensor for precision measurements Type P-30

Item number:	48807179
Quantity:	1 pcs.
Order code:	P-30-P-BA316-HDLZ-A-M4Z-ZZ W1011DA1-Z2L-2BGZMZZ-PGSDA
Overview:	P-30 ; 0...1.6 bar abs; 4...20 mA, 2-W @ 9...30 V DC; Accuracy: 0.1% of span G 1/4 A DIN EN ISO 1179-2 Sealing: FPM/FKM circular connector M12x1, 4-pin UB=1, 0V=3 shield: on case Specifications according to data sheet: PE 81.54
Details:	Pressure sensor for precision measurements Type P-30 Specifications according to data sheet: PE 81.54 Accuracy: 0.1% of span Measuring range: 0...1.6 bar abs Process connection: G 1/4 A DIN EN ISO 1179-2 Sealing: FPM/FKM Version for specific media: none Output signal: 4 ... 20 mA, 2-wire Electrical connection: circular connector M12x1, 4-pin www.wika.com Model name customer-specific: P-30 Pressure port: Standard Permissible medium temperature: -20...+105°C Pin assignment: UB=1, 0V=3 shield: on case Power supply: 9...30 V DC with test protocol *Made in Germany* on label WIKA standard - specification according to data sheet

© 2023 - WIKA Instruments s.a.r.l.