DATASHEET - M22-TC

Telescopic clip

Part no. M22-TC
216398

EL Number (Norway) 4355417

Product name	Eaton Moeller® series M22 Accessory Telescopic clip
Part no.	M22-TC
EAN	4015082163983
Product Length/Depth	80 millimetre
Product height	40 millimetre
Product width	30 millimetre
Product weight	0.031 kilogram
Compliances	CE Marked
Certifications	CSA Std. C22.2 No. 14-05 EN 60947-5 UL 508 CSA Std. C22.2 No. 94-91 IEC 60947-5 CSA UL File No.: E29184 IEC/EN 60947-5 CSA-C22.2 No. 94-91 CSA File No.: 012528 UL Category Control No.: NKCR CSA Class No.: 3211-03 CE UL CSA-C22.2 No. 14-05
Product Tradename	M22
Product Type	Accessory
Product Sub Type	Telescopic clip
Catalog Notes	Do not use in conjunction with emergency switching off actuators. for three contact/LED elements with base fixing maximum of 10 x M22-TC brackets per enclosure, five of which can hold stay-put actuators Steplessly adjustable, screw- and snap fixing (top-hat rail IEC/EN 60715).
Fitted with:	Centering adapter
Functions	For equalization of the mounting depth of rear mounting devices in CI enclosures, and in cabinets with mounting depths of 115 - 155 mm
Product category	Accessories
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	70 °C
Connection to SmartWire-DT	No
Equipment heat dissipation, current-dependent Pvid	0 W
Heat dissipation capacity Pdiss	0 W
Heat dissipation per pole, current-dependent Pvid	0 W
Rated operational current for specified heat dissipation (In)	0 A
Static heat dissipation, non-current-dependent Pvs	0 W
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Please enquire
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of assemblies			Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances			Meets the product standard's requirements.
10.5 Protection against electric shock			Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			Not applicable.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Accessories/spare parts for command devices (EC002024)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Command and alarm devices (accessories) (ecl@ss10.0.1-27-37-12-92 [ACO037010])			
Type of electrical accessory/spare part			Other
Type of mechanical accessory/spare part			Other

© 04/2023 by Eaton Industries GmbH