Set mit OBD-II-Buchse
Die Komponenten dienen zur Herstellung einer Leitung zum Anschluss an den OBD-II-Stecker im Fahrzeuginnenraum

Best.-Nr.
SET 8140 / OBD II / 24V / GB / 8 / SW
- Set mit Gehäuse aus PA6 mit Glaskugeln verstärkt, OBD-II-Buchse und Knickschutztülle für Kabel bis Ø 8 mm
- OBD-II-Buchse 24V mit Lötpins
- mit Lötanschluss für Litzendurchmesser bis max. Ø 1,3 mm
- Kontaktteile **vergoldet**


Best.-Nr.
SET 8140 / OBD II / 24V / GF / 8 / SW
- Set mit Gehäuse aus PA6 mit Glasfasern verstärkt, OBD-II-Buchse und Knickschutztülle für Kabel bis Ø 8 mm
- OBD-II-Buchse 24V mit Lötpins
- mit Lötanschluss für Litzendurchmesser bis max. Ø 1,3 mm
- Kontaktteile **vergoldet**


Set with OBD II socket
The components are used for the manufacture of a lead for connecting to the OBD II connector in the vehicle interior


Order No.
SET 8140 / OBD II / 24V / GB / 8 / SW
- *set with housing made of PA6 reinforced with glass beads, OBD II socket and bend relief for cables up to Ø 8 mm*
- *OBD II socket 24 V with solder pins*
- *with solder terminal for wire strand up to Ø 1.3 mm*
- *contact parts* ***gold-plated***

Order No.
SET 8140 / OBD II / 24V / GF / 8 / SW
- *set with housing made of PA6 reinforced with glass fibres, OBD II socket and bend relief for cables up to Ø 8 mm*
- *OBD II socket 24 V with solder pins*
- *with solder terminal for wire strand up to Ø 1.3 mm*
- *contact parts* ***gold-plated***









Allgemeine Angaben		
Best.-Nr. [1]	**SET 8140 / OBD II / 24V / GB / 8 / SW** Kontaktteile vergoldet	**SET 8140 / OBD II / 24V / GF / 8 / SW** Kontaktteile vergoldet
Farben	schwarz	
Gehäuse	PA 6 mit Glaskugeln verstärkt	PA 6 mit Glasfasern verstärkt
	UL94 – HB	UL94 – V0
Technische Daten		
Leitung	Ø 8 mm	
Durchgangswiderstand	-	
Bemessungsspannung [2]	24 V	
Bemessungsstrom [2]	10 A	
Temperatur-Einsatzbereich	von -40 °C bis +85 °C	

[1] andere Kontaktoberflächen, Farben und Anschlüsse auf Anfrage
[2] bei normalen Umgebungstemperaturen

General information		
Order No. [1]	***SET 8140 / OBD II / 24V / GB / 8 / SW*** *contact parts gold-plated*	***SET 8140 / OBD II / 24V / GF / 8 / SW*** *contact parts gold-plated*
colours	*black*	
housing	*PA 6 reinforced with glass beads*	*PA 6 reinforced with glass fibres*
	UL94 – HB	*UL94 – V0*
Technical data		
cable	*Ø 8 mm*	
transition resistance	-	
rated voltage [2]	*24 V*	
rated current [2]	*10 A*	
operating temperature	*from -40 °C to +85 °C*	

[1] *other contact platings, colours and terminals on request*
[2] *at normal ambient temperatures*