Date: 11/04/2023

TW20 P=33.4 mm G 1/2 female U=111 mm B=0.260 inch (6.6 mm) SS304/304L

Socket weld Thermowell TW20, solid machined

Item number: 48798416

Quantity: 1 pcs.

Order code: TW20-B-M-3-TD-00111-00045-G1-A-3-0190-0190-ZZ-3-Z00149 Z00149ZZYQ3Z
CERT31-EG3A-BB- - - - - - - - - - - TW-CT2

Overview:
TW20 P=33.4 mm G 1/2 female U=111 mm B=0.260 inch (6.6 mm) SS304/304L
Welding diameter: 33.4 mm
Connection to thermometer [N]: G 1/2 female
Thermowell style: Straight
Head length [H]: 45 mm
Insertion length [U]: 111 mm
Root diameter [Q]: 19 mm
Tip diameter [V or F3]: 19 mm
Bore size [B or d1]: 0.260 inch (6.6 mm)
Bore depth / stem length (US) [A]: 149 mm
Specifications according to data sheet: TW 95.20

Inspection certificate acc. to DIN EN 10204 3.1
Certificate Language: English and German
Thermowell / protection tube
Material certificate: Wetted parts material (metal contents) with mill certificate incl. chemical analysis

Details:
Socket weld Thermowell TW20, solid machined
Specifications according to data sheet: TW 95.20
Thermowell style: Straight
Unit of measure: Metric (mm)
Welding diameter: 33.4 mm (for 1 inch pipe)
Connection to thermometer [N]: G 1/2 female
Insertion length [U]: 111 mm
Head length [H]: 45 mm
Material: Stainless steel 304/304L
Bore size [B or d1]: 0.260 inch (6.6 mm)
Pressure rating: Class 3000
Root diameter [Q]: 19 mm
Tip diameter [V or F3]: 19 mm
Bore depth / stem length (US) [A]: 149 mm
Tip thickness [Tt]: 0.250 inch (6.4 mm)
Inspection certificate acc. to DIN EN 10204 3.1
Certificate Language: English and German

© 2023 - WIKA Instruments s.a.r.l.

Date: 11/04/2023

Thermowell / protection tube
Material certificate: Wetted parts material (metal contents) with mill certificate incl. chemical analysis

© 2023 - WIKA Instruments s.a.r.l.