# DATASHEET - NH2 SINGLE POLE PV



**Fuse base, high speed, 400 A, AC 690 V, 50 kA, NH2, 1P, IEC, UL, CSA**

**Part no.** NH2 SINGLE POLE PV
**Catalog No.** SD2-D-PV

Similar to illustration

## Delivery program

| | | | |
|---|---|---|---|
| Product range | | | Fuse accessory |
| Basic function | | | Fuse-base |
| Field of application | | | high speed |
| Rated current | I | A | 400 |
| Rated voltage | | | AC 690 V |
| Construction size | | | NH2 |
| Breaking Capacity | | kA | 50 |
| Number of poles | | | 1P |
| usable for size/applications | | | NH Photovoltaic fuse links |
| Standard/Approval | | | IEC<br>UL<br>CSA |
| Material | | | Glass-filled PBT body |
| Standards/Regulations | | | IEC 60269-1 |
| Optional accessories | | | Microswitches,Shroud kit, Phase barriers, Neutral links and Fuse extraction handle |

## Technical data ETIM 7.0

| | | | |
|---|---|---|---|
| Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse base (EC000067) | | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse systems / Low-Voltage HRC fuse base (ecl@ss10.0.1-27-14-21-06 [AKE278013]) | | | |
| Construction size | | | NH2 |
| Number of poles | | | 1 |
| Rated current | | A | 400 |
| Bus-mounting type | | | Yes |
| Swivelling mechanism | | | Yes |


© 02/2021 by Eaton Industries GmbH