Date: 12/04/2023

TCS2CA - 90 ... 160°C 1/2 NPT male 1/2 -14 NPT-F

compact temperature switch

Item number: 48735957

Quantity: 1 pcs.

Order code: TCS2CA-CAFC-EASZZZZGZZZ ZCK
C011000DZZZZZZZZ

Overview:
TCS2CA - 90 ... 160°C 1/2 NPT male 1/2 -14 NPT-F
compact temperature switch TCS
switch enclosure: aluminium,copper-free
sensor version: remote mounting with capillary, length 2 m
contact version: 1xSPDT, silver contact
setting range: 90 ... 160°C, working range -40 ... +170°C, proof temperature +180°C
Set point definition: Set Point customer-specifically configured
Process connection: 1/2 NPT male
Electrical connection: 1/2 -14 NPT-F
Mounting: standard direct or wall mounting, fixing bore on the case
Sensor Dimensions: active length X = 55 mm, insertion length Ymin = 100 mm, Ymax = 350 mm, bulb diameter D=9,5 mm
Brand: WIKA Instruments Italia
Ingress Protection: IP66
Specifications according to data sheet: TV 31.64
Repeatability of set point: ≤ 1% of span
1. set point: 110.00 °C decreasing,

Details:
compact temperature switch
model TCS
Specifications according to data sheet: TV 31.64
Repeatability of set point: ≤ 1% of span
switch enclosure: aluminium,copper-free
sensor version: remote mounting with capillary, length 2 m
1xSPDT, silver contact
90 ... 160°C, working range -40 ... +170°C, proof temperature +180°C
Set Point customer-specifically configured
Process connection: 1/2 NPT male
Electrical connection: 1/2 -14 NPT-F
standard direct or wall mounting, fixing bore on the case
Sensor Dimensions: active length X = 55 mm, insertion length Ymin = 100 mm, Ymax = 350 mm, bulb diameter D=9,5 mm
Brand: WIKA Instruments Italia
Ingress Protection: IP66
Unit: °C
TCS2CA
1. set point: 110.00 °C decreasing,

© 2023 - WIKA Instruments s.a.r.l.