DATASHEET - M30C-FUSB

Bulkhead interface, with permanently connected USB 3.0 Type A plug, Metal bezel

Part no.	**M30C-FUSB**
	187082
EL Number (Norway)	**4315737**

Product name	Eaton Moeller® series M30 Accessory Bulkhead interface
Part no.	M30C-FUSB
EAN	4015081821396
Product Length/Depth	50 millimetre
Product height	55 millimetre
Product width	46 millimetre
Product weight	0.05 kilogram
Compliances	CE
Product Tradename	M30
Product Type	Accessory
Product Sub Type	Bulkhead interface
Bezel color	Metal
Design	USB 3.0 A
Fitted with:	Permanently connected USB 3.0 Type A plug
Number of poles	Nine-pole
Degree of protection	IP20 (with plug connected) IP65, with closed cover
Lifespan, mechanical	100 insertion cycles
Limit value class	3
Mounting depth	27 mm
Opening diameter	30.5 mm
Product category	Pilot Devices
Size	30 mm
Used with	M22 contact blocks and indicating lights
Ambient operating temperature - min	-20 °C
Ambient operating temperature - max	70 °C
Ambient storage temperature - min	25 °C
Ambient storage temperature - max	70 °C
Insulation resistance	≥ 100 MΩ
Nominal current	900 A
Nominal voltage - max	30 V
Rated operational voltage	5 V AC/DC
Resistance	< 30 mΩ (volume resistance)
Connection to SmartWire-DT	No
Data transfer rate	5 GBit/s, max.
Contact material	CuSn, gold-plated
Contact type	1:1
Force for positive opening - min	0 N

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Accessories/spare parts for command devices (EC002024)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Command and alarm devices (accessories) (ecl@ss10.0.1-27-37-12-92 [ACO037010])			
Type of electrical accessory/spare part			Other
Type of mechanical accessory/spare part			Other

© 04/2023 by Eaton Industries GmbH