**datasheet for SAB 2600 G M4 Au**
**article number: 972357702**

| **product description:** | order number: 972 357-702 |
|---|---|
| **description:** | built-on socket, 4 mm diameter, contact-protected, gold-plated brass with M4 thread.<br>For installation into switch-panels and equipment-chassis of 1-4mm thickness.<br>Connects with safety test leads. |
| **typ:** | SAB 2600 G M4 Au blau/blue |
| **system:** | 4 mm safety system |
| **order number:** | 972 357-702 |
| **color** | |
| **other color versions:** | |
| **technical data** | |
| **measurement category acc. to IEC 61010:** | CAT II |
| **type of contact:** | unsprung socket Ø 4 mm |
| **type of termination:** | M4 thread |
| **rated voltage:** | AC/DC 1000 V |
| **rated current:** **Please consider derating curve!** | 32 A |
| **contact resistance:** | 5 mOhm |
| **mounting:** | screw |
| **material** | |
| **contact material:** | brass |
| **contact surface material:** | gold |
| **housing material:** | PA |
| **environmental conditions:** | |
| **temperature range:** | -25°C to +70°C |
| **inflammable class:** | |
| **housing (basic material):** | UL 94 V-2 |

*Copyright ©2015 SKS Kontakttechnik GmbH / Neue Schichtstr. 14 / D-09366 Niederdorf (printed: Thu May 28 2015 9:44:51)*