
OPL204

Photoelectric angle sensor

OPL-DPKG/US



Product characteristics		
Type of light		red light
Application		
Special feature		Function check output
Electrical data		
Operating voltage	[V]	10...35 DC; ("supply class 2" to cULus)
Current consumption	[mA]	< 45
Protection class		III
Reverse polarity protection		yes
Type of light		red light
Wave length	[nm]	660
Outputs		
Electrical design		PNP
Output function		dark-on mode
Max. voltage drop switching output DC	[V]	2
Function check output		yes
Permanent current rating of switching output DC	[mA]	200
Switching frequency DC	[Hz]	200

OPL204

Photoelectric angle sensor

OPL-DPKG/US

Short-circuit protection		yes	
Type of short-circuit protection		pulsed	
Overload protection		yes	
Operating conditions			
Ambient temperature	[°C]	-10...60	
Protection		IP 67	
Tests / approvals			
EMC		EN 60947-5-2	
MTTF	[years]	919	
Mechanical data			
Weight	[g]	150	
Dimensions	[mm]	65 x 10 x 106	
Side length X	[mm]	54	
Side length Y	[mm]	55	
Sensor width Z	[mm]	60.46	
Materials		housing: diecast zinc; lens: glass	
Displays / operating elements			
Display		switching status	1 x LED, yellow
		operation	1 x LED, green
		function	1 x LED, yellow
Remarks			
Pack quantity		1 pcs.	
Electrical connection			

Connector: 1 x M12; coding: A




OPL204

Photoelectric angle sensor

OPL-DPKG/US

Connection



2	Function check output