VENTILATION ELEMENT SET

BEL Air M40



BEL Air M40

Ventilation element set

Article number: 26344001

BEL Air ventilation element set, For preventing condensation build-up in housings, For vertical installation in housing walls and GFL combi flanges with corresponding knock-outs, At least two ventilation elements are required per housing

M40, Set = 2 pcs., Air exchange rate: 30 l / day / set

IP65 IK08

Technical data

Material:

material:	Polycarbonate
Lock nut:	polyamide, fiberglass-reinforced
Material::	Polycarbonate
Conncation thread ring:	polyethylene

Environmental attributes

Ambient temperature (max.):	80 °C
Ambient temperature (24 h):	60 °C
Ambient temperature (min.):	-35 °C

Günther Spelsberg GmbH + Co. KG · Im Gewerbepark 1 · D-58579 Schalksmühle · Germany · Phone: +49 (0) 23 55 / 892-0 · Fax: +49 (0) 23 55 / 892-299

VENTILATION ELEMENT SET

BEL Air M40

Other attributes

Ingress protection:	IP65 - acc. to EN 60529 / DIN VDE 0470-1
Impact resistance:	IK08 acc. DIN EN 5012 / VDE 0470 segment 100
UL Type Rating:	3R, 12, 12K as per UL50, CSA C22.2
with lock nut:	Yes
Color:	Green
Thread lenght/mm:	11
Heavy metals-free:	Yes
Thread:	M40 x 1.5
PVC-free:	Yes
Silicone-free:	Yes

Günther Spelsberg GmbH + Co. KG · Im Gewerbepark 1 · D-58579 Schalksmühle · Germany · Phone: +49 (0) 23 55 / 892-0 · Fax: +49 (0) 23 55 / 892-299