# Product data sheet
## Characteristics

# ZCKS1H29
limit switch body ZCKS - 1NC+1NO - snap action - M20




## Main

| | |
|---|---|
| Range of product | OsiSense XC |
| Series name | Standard format |
| Product or component type | Limit switch body |
| Device short name | ZCKS |
| Body type | Fixed |
| Product compatibility | XCKS |
| Associated head | ZCKD01<br>ZCKD019<br>ZCKD02<br>ZCKD05<br>ZCKD06<br>ZCKD08<br>ZCKD31<br>ZCKD33<br>ZCKD34<br>ZCKD39<br>ZCKD41<br>ZCKD49<br>ZCKD54<br>ZCKD55<br>ZCKD59<br>ZCKD81<br>ZCKD91<br>ZCKD029 |
| Body material | Plastic |
| Cable entry | 1 entry tapped for M20 x 1.5 cable gland |
| Number of poles | 2 |
| Contacts type and composition | 1 NC + 1 NO |
| Contact operation | Snap action |
| Number of steps | 1 1 position |
| Contacts material | Silver plated contacts |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Complementary

| | |
|---|---|
| Local display | Without |
| Electrical connection | Screw-clamp terminals, clamping capacity: 1 x 0.34...2 x 1.5 mm² |
| Positive opening | With |
| Minimum actuation speed | 0.01 m/min |
| [Ie] rated operational current | 3 A at 240 V, AC-15, A300 conforming to EN/IEC 60947-5-1 appendix A<br>0.27 A at 250 V, DC-13, Q300 conforming to EN/IEC 60947-5-1 appendix A |
| [Ithe] conventional enclosed thermal current | 10 A |
| [Ui] rated insulation voltage | 300 V conforming to CSA C22.2 No 14 contact block<br>300 V conforming to UL 508 contact block<br>500 V degree of pollution 3 conforming to IEC 60947-1 contact block |
| Resistance across terminals | 0.25 mOhm conforming to IEC 60255-7 category 3 |
| [Uimp] rated impulse withstand voltage | 6 kV conforming to IEC 60664<br>6 kV conforming to IEC 60947-1 |
| Short-circuit protection | 10 A by gG cartridge fuse |
| Electrical durability | 5000000 cycles, DC-13 120 V, 7 W, operating rate: < 60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C<br>5000000 cycles, DC-13 24 V, 13 W, operating rate: < 60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C<br>5000000 cycles, DC-13 48 V, 9 W, operating rate: < 60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C |
| Width | 40 mm |
| Height | 73 mm |
| Depth | 36 mm |
| Product weight | 0.08 kg |
| Terminals description ISO n°1 | (11-12)NC<br>(21-22)NC |

## Environment

| | |
|---|---|
| IP degree of protection | IP65 |
| IK degree of protection | IK03 |
| Ambient air temperature for operation | -25...70 °C for standard environment |
| Ambient air temperature for storage | -40...70 °C |
| Environmental characteristic | Standard environment |

## Offer Sustainability

| | |
|---|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 1008 - Schneider Electric declaration of conformity<br>Schneider Electric declaration of conformity |
| REACh | Reference not containing SVHC above the threshold<br>Reference not containing SVHC above the threshold |
| Product environmental profile | Available<br>Product environmental |
| Product end of life instructions | Available<br>End of life manual |

## Contractual warranty

| | |
|---|---|
| Warranty period | 18 months |