DATASHEET - CDAE-01/04

Smart Dimming Actuator, R/L/C/LED, 0-250W, 230VAC

Part no.	**CDAE-01/04**
	182446
EL Number (Norway)	**4560739**

General specifications	
Product name	Eaton Moeller series xComfort dimming actuator
Part no.	CDAE-01/04
EAN	4015081773732
Product Length/Depth	149.63 millimetre
Product height	27.7 millimetre
Product width	34.06 millimetre
Product weight	0.06 kilogram
Compliances	RoHS conform
Product Tradename	xComfort
Product Type	Dimming actuator
Product Sub Type	None
Delivery program	
Model	Dimming actuator
Actuation function	Dimming
Bus system operating type	xComfort Radio frequent
Bus system product type	Actuator
Technical Data - Electrical	
Voltage rating - min	230 V
Voltage rating - max	230 V
Rated control supply current Is	0 mA
Frequency rating - min	50 Hz
Frequency rating - max	50 Hz
Load type	Universal and LED retrofit
Power supply	Mains
Output power - min	0 W
Output power - max	250 W
Technical Data - Mechanical	
Width in number of modular spacings	3
Mounting method	Built-in Built-in installation
Number of outputs	1
Degree of protection	IP20
Additional information	
Features	Radio frequent bidirectional
Fitted with:	LED indication Bus connection

Technical data ETIM 9.0

Installation bus systems (EG000032) / Dimming actuator for bus system (EC001094)	
Electric engineering, automation, process control engineering / Electrical installation, device / Bus system / Bus system dimming actuator (ecl@ss13-27-14-31-23 [AKE291020])	
Bus system KNX	No
Bus system KNX-RF (Radio Frequent)	No
Bus system radio frequent	Yes
Bus system LON	No
Bus system Powernet	No
Other bus systems	xComfort

Radio frequent bidirectional		Yes
Model		Dimming actuator
Mounting method		Built-in installation
Width in number of modular spacings		3
With bus connection		Yes
Bus module detachable		No
Substation input		No
Local operation/hand operation		No
With LED indication		Yes
Number of outputs		1
Output power	W	0 - 250
Power boost suitable		No
Type of load		Universal and LED Retrofit
Max. control current	mA	0
Max. switching power LED	W	100
Voltage	V	230 - 230
Parallel-service possible		No
Frequency	Hz	50 - 50
Degree of protection (IP)		IP20
Min. depth of built-in installation box	mm	0
Compatible with Casambi		No

© 04/2023 by Eaton Industries GmbH