Specifications

Eaton 194618



Catalog Number: 194618

Eaton xEnergy Safety Ci LV systems LV switchgear. Covers, RAL7035, HxWxD=250x187.5x25mm

General specifications

Product Name
Eaton xEnergy Safety Ci empty enclosure cover opaque

Catalog Number
194618

EAN
9010238059269

Product Length/Depth
30 mm

Product Height
250 mm

Product Width
187.5 mm

Product Weight
0.326 kg

Compliances
RoHS conform

Powering Business Worldwide

Product specifications

Used with

U-CI23…

Basic enclosure

xEnergy Safety Ci

Enclosure cover

Special features

Sealable cover fasteners

Type

Basic enclosure

Enclosure cover

xEnergy Safety Ci

Accessory/spare part type

Enclosure cover without apertures

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility.

10.13 Mechanical function

Meets the product standard's requirements.

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

850 °C; meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Not relevant to indoor installations.

10.2.5 Lifting

5 kg per enclosure with support frame and lifting aid met; assembled and secured as per the latest applicable instruction

Resources

Brochures

eaton-xenergy-safety-ci-subway-line-success-story-en-us.pdf

eaton-xenergy-safety-ci-enclosure-brochure-br014001en-en-us.pdf

Catalogs

eaton-xenergy-ci-safety-catalog-ca015006en-en-us.pdf

Drawings

eaton-enclosures-xenergy-safety-ci-cover-3d-drawing-003.eps

Installation instructions

05670392.pdf

mCAD model

d125_ci23_ral7035.dwg

d125_ci23_ral7035.stp

leaflet.

10.2.6 Mechanical impact

IK10

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

IP65, with base unit

10.4 Clearances and creepage distances

Is the panel builder's responsibility.

10.5 Protection against electric shock

Protection class 2, therefore not applicable.

10.6 Incorporation of switching devices and components

Is the panel builder's responsibility.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Ui = 1000 V AC

10.9.3 Impulse withstand voltage

8 kV

10.9.4 Testing of enclosures made of insulating material

Meets the product standard's requirements.

Surface finishing

Other

Color

Gray

Non Transparent, RAL 7035, light gray

Unit type

Modular system

Heat diss. ambient 35°C delta T:20°C wall mount individ. encl. top (IEC 60890)

6 W

Heat diss. ambient 35°C delta T: 20°C wall mount middle encl. top (IEC 60890)

6 W

Heat diss. ambient 35°C delta T:20°C wall mount starting encl. top (IEC 60890)

6 W

Heat diss. ambient 35°C delta T:35°C wall mount individ. encl. top (IEC 60890)

13 W

Heat diss. ambient 35°C delta T: 35°C wall mount middle encl. top (IEC 60890)

12 W

Heat diss. ambient 35°C delta T:35°C wall mount starting encl. top (IEC 60890)

12 W

Mounting depth

125 mm

RAL-number

7035

Suitable for enclosure building length/depth

125 mm

Suitable for enclosure building width

187.5 mm

Cover/door type

Non-transparent

Material

Plastic

Suitable for

Outdoor set-up

Functions

Basic enclosure

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia