STBT4

Suretime 2 Hour Electronic Boost Timer



Features & Benefits

- Typical applications - Immersion Heaters - Room Heaters - Towel Rails - Lighting
- Various Boost Options
- Automatic timer countdown for up to 2 hours.
- Cancellation of countdown time by pressing the boost button mid-cycle.
- Bright illumination of the boost button at all times.
- Minimalist and simple to use!
- LED indicators for approximate time left on countdown.
- Ideal for immersion control systems not racking up a huge bill.
- Fits a standard flush or surface BS wall box with 25mm depth.

Technical Data

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Surface
Earth Class Rating	Class II
Operating Temperature	0°C to 45°C
Ingress Protection Rating	IP20
Setting Type	Button Press
Back Box Minimum Depth (mm)	25
Push Buttons	Yes (Boost Button)
Mounting Hole Centres (mm)	60

Standby Consumption	<1W
Number of Channels	1
Switch rating	13A Resistive, 80W LED, 1000W Halogen, 500W Fluorescent, 100W Low Energy Lighting
Shortest Switching Time	15 Minutes
Time Delay Range	15 Min, 30 Min, 1 Hour, 2 Hours
Permanent ON Facility	No
Multiple Unit Support	No
Cable Entry(s)	Back Entry, Bottom Entry

General

Weight (g)	113
Height (mm)	85
Width (mm)	85
Depth (mm)	31
Body Construction	Polycarbonate
Product Colour	White
Accessories (Included)	Screws
EAN Number	5012483015285
Guarantee Period	2 Years
Trade Tariff Commodity Code	8536508090

Data sheet
STBT4

Time / Immersion & General Purpose Timeswitches

Line Diagrams



