Date: 11/04/2023

TW15-H 1NPT G 1/2 female U=80 mm B=0.335 inch (8.5 mm) SS316/316L

Threaded Thermowell TW15, solid machined

Item number:	48716499
Quantity:	1 pcs.
Order code:	TW15-H-A-M-NF-TD-00080-00046-G3-M-0270-0190-ZZ-ZZ00119 Z00119HZZZYQ2Z
Overview:	TW15-H 1NPT G 1/2 female U=80 mm B=0.335 inch (8.5 mm) SS316/316L Process thread [P or E]: 1NPT Connection to thermometer [N]: G 1/2 female Thermowell style: Tapered Head length [H]: 46 mm Insertion length [U]: 80 mm Root diameter [Q]: 27 mm Tip diameter [V or F3]: 19 mm Bore size [B or d1]: 0.335 inch (8.5 mm) Bore depth / stem length (US) [A]: 119 mm Specifications according to data sheet: TW 95.15
Details:	Threaded Thermowell TW15, solid machined Specifications according to data sheet: TW 95.15 Head design: Hexagon Thermowell style: Tapered Unit of measure: Metric (mm) Process thread [P or E]: 1 NPT Connection to thermometer [N]: G 1/2 female Insertion length [U]: 80 mm Head length [H]: 46 mm Material: Stainless steel 316/316L Bore size [B or d1]: 0.335 inch (8.5 mm) Root diameter [Q]: 27 mm Tip diameter [V or F3]: 19 mm Bore depth / stem length (US) [A]: 119 mm Tip thickness [Tt]: 0.250 inch (6.4 mm)

© 2023 - WIKA Instruments s.a.r.l.