Specifications

Eaton 216552

Catalog Number: 216552

Eaton Moeller® series M22 Shroud, for flush mounting plate, 5 mounting locations



General specifications

Product Name
Eaton Moeller® series M22 Accessory Shroud

Catalog Number
216552

EAN
4015082165529

Product Length/Depth
150 mm

Product Height
80 mm

Product Width
110 mm

Product Weight
0.196 kg

Certifications
UL Category Control No.: NKCR
CE
UL
CSA
UL 508
UL File No.: E29184
CSA Class No.: 3211-03
CSA File No.: 012528
CSA-C22.2 No. 14-05
CSA-C22.2 No. 94-91
IEC/EN 60947-5

Powering Business Worldwide

Features & Functions

Color
Gray

Knockouts
5 x M20 (cable entry knockouts at the base)

Material
Insulated material light

Number of locations
5

RAL-number
7035

General

Degree of protection
NEMA 4X

IP40

Protection
Protection type only in combination with flush mounting plates M22-E…

Climatic environmental conditions

Ambient operating temperature - min
-25 °C

Ambient operating temperature - max
70 °C

Communication

Connection to SmartWire-DT
No

Contacts

Force for positive opening - min
0 N

Design verification

Equipment heat dissipation, current-dependent Pvid
0 W

Heat dissipation capacity Pdiss
0 W

Heat dissipation per pole, current-dependent Pvid
0 W

Rated operational current for specified heat dissipation (In)
0 A

Static heat dissipation, non-current-dependent Pvs
0 W

10.2.2 Corrosion resistance
Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures
Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Resources

Catalogs
eaton-rmq-titan-brochure-br047004en-en-us.pdf

eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf

Flip catalog - Product Range Catalog - Command and indication

Declarations of conformity
DA-DC-00004135.pdf

DA-DC-00004157.pdf

Drawings
eaton-operating-shroud-m22-dimensions-011.eps

eaton-operating-shroud-m22-dimensions-005.eps

eaton-operating-shroud-m22-3d-drawing-005.eps

eaton-operating-button-symbol-007.eps

eCAD model
ETN.216552.edz

Installation instructions

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Please enquire

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

Not applicable.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the

IL04716003Z

Installation videos

RMQ Flat Design

mCAD model

DA-CS-einbauhaube_gr_5

DA-CD-einbauhaube_gr_5

Multimedia

MCI Multicolor Light Indicator M22 with SmartWire-DT

RMQ small E-Stop emergency-stop button

MCI MultiColor Light Indicator RMQ compact solution

easyE4 SmartWire-DT module with Remote Touch Display and RMQ multi color indicator

Sales notes

eaton-control circuit-devices rmq-titan-fl144090en-en-us.pdf

eaton-rmq-flat-enclosure-flyer-fl047003en-en-us.pdf

eaton-rmq-small-e-stop-flyer-fl047006en-en-us.pdf

eaton-rmq-mci-multi-color-light-indicator-flyer-fl047005en-en-us.pdf

System overview

Pilot devices - selection aid

switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia