British Plug Top Fuse
Fast-Acting

TDC600



Dimensional Data



Catalog Symbol: TDC600
Fast-Acting, High Braking Capacity Fuse
600 Volts AC
BS1362, UL Recognized

Limits for Pre-arcing Time

	1.0 In.	1.6 In.	1.9 In.
In	**MIN**	**MIN**	**MAX**
2A, 10A	1000 hours	30 min.	30 min.

Electrical Ratings (Catalog Symbol and Amperes)

600 Volts	
TDC600-2A	TDC600-10A

Rated Current	Rated Voltage (V)	Breaking Capacity	Power Dissipation (W)	Color	Approvals
2A 10A	600	200A,600V 10kA, 250V p.f. 0.7 - 0.8	1 Watt @ Rated Current	Blue	Asta, BSI

Time-Current Characteristic Curves
Average Melt (Full Size Curves Available)



- **Type TDC600.**
- 1/4" x 1" fast-acting, high breaking capacity fuse.
- Ceramic tube - end caps: silver-plated copper.
- Packaging: x 10, x 100, x 1000.
- Weight: 2.5g.

The only controlled copy of this Data Sheet is the electronic read-only version located on the Bussmann Network Drive. All other copies of this Data Sheet is are by definition uncontrolled. This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Bussmann reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Bussmann also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.