Date: 22/01/2024

LH-10 ; ## 0...3 mWG ##; 4...20 mA, 2-W

Level Probe Model LH-10

Item number:

Quantity:	1 pcs.	
Order code:	LH-10-A-B##-GD-KG-ZZZ	W101-ZZZZZZ-F2D-GSE5
Overview:	LH-10 ; ## 0...3 mWG ##; 4...20 mA, 2-W @ 10 ... 30 V DC; Accuracy: 0.25% of span (with pressure ranges < 250 mbar: 0.5% of span) G1/2B FEP cable Cable length: 5 m UB=BN, 0V=GN Specifications according to data sheet: PE 81.09	
Details:	Level Probe Model LH-10 High performance version Specifications according to data sheet: PE 81.09 Accuracy: 0.25% of span (with pressure ranges < 250 mbar: 0.5% of span) Permissible medium temperature: -10...+50°C (+14...+122°F); with FEP cable -10...+85°C (+14...+185°F) Ingress protection: IP 68 Special protection: Longitudinal water resistance Output signal: 4 ... 20 mA, 2-wire Measuring range: ## 0...3 mWG ## Process connection: G 1/2 B Special design features: FEP cable Cable length: 5 m WIKA standard Power supply: 10 ... 30 V DC Pin assignment: UB=BN, 0V=GN *Made in Germany* on label WIKA standard - specification according to data sheet	

© 2024 - WIKA Instruments s.a.r.l.