Specifications

Eaton 2D27R



Catalog Number: 2D27R

Eaton Fuse-link, LV, 2 A, AC 500 V, D2, gR, IEC, ultra rapid

General specifications

Product Name
Eaton Bussmann series low voltage D fuse

Catalog Number
2D27R

EAN
5027590472494

Product Length/Depth
50 mm

Product Height
22 mm

Product Width
22 mm

Product Weight
27.92 g

Compliances
CE Marked
RoHS Compliant

Certifications
IEC 60269
EAC
DIN EN 60269-3 (VDE 0636 Part 30)
DIN EN 60269-1 (VDE 0636 Part 10)
DIN VDE 0636-301

Powering Business Worldwide

Product specifications

Type

Fuse

Application

For domestic and general industrial applications

Amperage Rating

2 A

Fuse size

DII

Breaking capacity

50 kA

Construction size (fuse inserts)

DII

Rated voltage AC

500 V

Class

Class gR

Fuse type

D27R - Ultra rapid

Accessory/spare part type

2GD27 Pink screw cap gauge piece

Utilization category

gR (general purpose semiconductor protection)

Color

Pink

Interrupt rating

50 kAIC

Fuse indicator

Non-indicating

Connection

Other

Construction

D2

Construction size

DII

Fuse shape

Resources

Brochures

eaton-bussmann-series-d-and-d0-fuses-product-aid-pa132014en-en-us.pdf

Catalogs

CA134002EN

Declarations of conformity

CE Bottle fuse-links, holders, carriers and accessories

UKCA Bottle fuse-links, holders, carriers and accessories

Technical service bulletins

Datasheet - 2D27R

Bottle

Response time

Ultra rapid

Suitable for

E27/DII Fuse base

TFD27 Fuse base screw fixing

SFRD27 Fuse base DIN-Rail mount

TFRD27 Fuse base DIN-Rail mount

Material

White ceramic body

Release characteristic

Super fast (FF)

Voltage rating

500 V

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia