Date: 10/04/2023

S-11 ; -1 ... +3 bar; 4...20 mA, 2-W

Pressure transmitter for general applications

Item number: 14075807

Quantity: 1 pcs.

Order code: S-11-A-BCH-86-Q1ZGM4ZAZ-ZZZ W101Z-ZZ-F2BSZZ-ZFOSE3

Overview:
S-11 ; -1 ... +3 bar; 4...20 mA, 2-W
@ 10 ... 30 V DC; Accuracy: 0.5% of span
G 1/2 B, flush diaphragm with O-ring
Wetted parts: stainless steel
Sealing: NBR;
circular connector M12x1, 4-pin UB=1, 0V=3
Permissible medium temperature: -30 ... +100 °C (-22 ... +212 °F)
Specifications according to data sheet: PE 81.02

Details:
Pressure transmitter for general applications
Model S-11
with flush diaphragm
Specifications according to data sheet: PE 81.02
Power supply: DC 10 (14) ... 30 V
Case: stainless steel
Output signal: 4 ... 20 mA, 2-wire
Measuring range: -1 ... +3 bar
Process connection: G 1/2 B, flush diaphragm with O-ring
Wetted parts: stainless steel
Sealing: NBR
Accuracy: 0.5% of span
Electrical connection: circular connector M12x1, 4-pin
Permissible medium temperature: -30 ... +100 °C (-22 ... +212 °F)
Power supply: 10 ... 30 V DC
Pin assignment: UB=1, 0V=3
shield: standard
WIKA standard - specification according to data sheet
Test protocol: without test protocol
Certificates: without
Import documentation CIS-States: without

© 2023 - WIKA Instruments s.a.r.l.