Date: 25/04/2023

PGS23.100...LM-D30 10 bar G1/2B

switchGAUGE PGS23.100/160

Item number: 48694890

Quantity: 1 pcs.

Order code: PGS23.100.212ZZPZ-BG410Z-GD-LM-D30ZZZZIZ-ZZZZ ZZZ 213DZ3HZIHG0 ZZZ-ZZZZZZ11Z

Overview:
PGS23.100...LM-D30 10 bar G1/2B
Alte Typenbezeichnung 23x.30.100
magnetic snap action switch, model 821.12
plug sidewise
Case: solid front design EN837 "S3"
Connection location: LM
class 1.0
Window: laminated safety glass
Ingress protection: IP 65
Permissible medium temperature: -20 ... +200 °C (-4 ... +392 °F)
Permissible ambient temperature: -20 … +60 °C
Pressure Gauge Standard: International (standard Europe)
WIKA Serial number *...*

Details:
switchGAUGE PGS23.100/160
pressure gauge with switches,
bourdon tube measuring system, stainless steel
Specifications according to data sheet: PV 22.02 and AC 08.01
switch: magnetic snap action switch, model 821
first switch operation: makes (1)
second switch operation: breaks (2)
Electrical connection: plug sidewise
Nominal size: 100
Measuring range: gauge pressure range
Scale range: 0...10 bar
Process connection: G 1/2 B
Connection location: lower mount
Liquid Damping (case filling): without filling
Case: solid front design EN837 "S3"
Pressure Gauge Standard: International (standard Europe)
Accuracy class: class 1.0
Overpressure safe: standard
Case material: Stainless steel 1.4301
Case surface: bare
Material pressure element: Measuring System 316L
Window: laminated safety glass
Ingress protection: IP 65
Permissible medium temperature: -20 ... +200 °C (-4 ... +392 °F)

© 2023 - WIKA Instruments s.a.r.l.

Permissible ambient temperature: -20 … +60 °C
Movement: stainless steel
Manufacturer logo: *WIKA*
serial number on dial: Serial number *...*

© 2023 - WIKA Instruments s.a.r.l.