# P5X14E110UL

UNDERVOLTAGE TRIP RELEASE FOR P5ME UL CERTIFIED, 110…130VAC/DC




| | |
|---|---|
| Product designation | Undervoltage trip |
| Product type designation | P5X14E110UL |
| Description | Undervoltage trip releases for UL certified MCCBs. |
| Accessories for | Accessories for UL-compliant MCCBs |

| Operational characteristics | | | |
|---|---|---|---|
| Rated supply voltage AC | | VAC | 110…130 |
| Rated supply voltage DC | | VDC | 110…130 |
| Rated frequency | | Hz | 45…65 |
| Holding consumption | | VA | 0.73 |
| Release voltage | | Us | 35…70 |
| Operating voltage | | US | 85…110 |
| Average opening time | | ms | 50 |
| **Mechanical features** | | | |
| Tightening torque for terminals | | | |
| | min | Nm | 0.8 |
| | max | Nm | 1 |
| | min | lbin | 7 |
| | max | lbin | 9 |
| Conductor section | | | |
| AWG/Kcmil | | | |
| | min | | 20 |
| | max | | 16 |
| Flexible w/o lug conductor section | | | |
| | min | mm² | 0.5 |
| | max | mm² | 1.5 |
| Flexible c/w lug conductor section | | | |
| | min | mm² | 0.5 |
| | max | mm² | 1.5 |
| Terminals | | | |
| | type | | Screw |
| | tool | | PZ2 |
| Weight | | g | 50 |


The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding




## Wiring diagrams

## Certifications and compliance

Certificates

cULus

## ETIM classification

EC000066 - Power contactor, AC switching


The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding