CAT. N° 4 105 76



ADD-ON MODULES DX³ - 2P 230 V~ - 63 A - 30 MA - HPI TYPE - FOR 1.5 MODULES DX³ MCB

Pack (number of units)	1
Volume (dm³)	2,095
Weight (g)	326,00

Product characteristics

2-pole - 230 V~

F type (old Hpi type)

- Sensitivity : 30 mA
- Nominal rating In : 63 A
- Number of modules : 2

General characteristics

Add-on modules DX³ - for 1.5 module/pole DX³ MCBs

- Conform to IEC 61009-1, IEC 62423 (F type)
- Voltage independent tripping except Cat.Nos 4 106 57/58/59
- AC type : detect AC components faults
- F type (High immunity) : detect faults with AC and DC components, increased immunity to false tripping
- Detection of high frequency fault currents
- For mounting on the right-hand side of 1.5 module per pole DX³ MCBs

Documentation

Catalogue pages & additional information

- Description page (p.071)
- Dimensions of din-rail equipment
- Performance of MCBs and auxiliaries

Installation & technical data

- F01221EN-04

Installation instructions & related documents

- LE03604ABDX3BDAHPFo

Environmental product profile

- Environnemental product sheet n°8 E0079A-FR
- LGRP-00738-V01

* All prices given are the manufacturer's list prices for professional customers, and are given for information only. They are not to be considered as a mandatory retail price - Basis : before-tax price list, May 2018

The information given in this e-catalogue (characteristics and dimensions) may be amended, and therefore does not represent an undertaking on our part. The e-catalogue is reserved for professionals only. You are also reminded that all products must be installed by a qualified professional in accordance with the installation rules.