*Date: 23/01/2024*

# A52.080/1, -20...+60°C, 160x8mm

## Bimetal Thermometer, Industrial Series

| | |
|---|---|
| Item number: | 3512843 |
| Quantity: | 1 pcs. |
| Order code: | A52.080-1-CBB-BS-C160GZZ-Z-ZZZ TD FZZVC-AZ1ZZZZZZZZZZ |
| Overview: | A52.080/1, -20...+60°C, 160x8mm<br>Process connection: plain, with neck to fit thermowell (thermowell necessary for mounting)<br>flat instrument glass<br>*WIKA* |
| Details: | Bimetal Thermometer, Industrial Series<br>Specifications according to data sheet: TM 52.01<br>Accuracy class: class 1 per EN 13190<br>Case: stainless steel<br>Stem material: stainless steel<br>Model: A52.080, nominal size 80, location of stem centre back<br>Connection design: 1, plain stem<br>Scale range: -20 °C ... +60 °C<br>Process connection: plain, with neck to fit thermowell (thermowell necessary for mounting)<br>Stem diameter: 8 mm<br>Insertion length L1: 160 mm<br>norm-mark on dial: *EN 13190*<br>accuracy class on dial: *Cl.1*<br>Bimetallic thermometer, for industrial applications A52L<br>Specifications according to data sheet: TM 52.01<br>Accuracy class: class 1 per EN 13190<br>Case: stainless steel<br>Stem material: stainless steel<br>Model: A52.080, nominal size 80, location of stem centre back<br>Connection design: 1, plain stem<br>Scale range: -20 °C ... +60 °C<br>Process connection: plain, with neck to fit thermowell (thermowell necessary for mounting)<br>Stem diameter: 8 mm<br>Insertion length L1: 160 mm<br>Window: flat instrument glass<br>Case: Stainless steel<br>Ingress protection: IP 43<br>Manufacturer logo: *WIKA*<br>Stem material: stainless steel |

*© 2024 - WIKA Instruments s.a.r.l.*