Date: 11/04/2023

Digital indicator model DI25

Digital indicator model DI25

Item number:	14070178
Quantity:	1 pcs.
Order code:	DI25-M-LP24KZB-
Overview:	Digital indicator model DI25 Input: multi-function input (input configuration setable) setable input configurations: Pt100, thermocouples type K/J/R/S/B/E/T/N/PL-II/C, 0/4...20 mA, 0...1/5/10 V, 1...5 V Power supply: AC/DC 24 V Output configuration: transmitter supply (DC 24 V max. 30 mA) and 2 alarm outputs Terminal cover: fixed with screws (protection against contact)
Details:	Digital indicator model DI25 Specifications according to data sheet: AC 80.02 Dimensions: 96 x 48 x 110 mm (installation depth: 98 mm) Ingress protection: IP 66 only case ingress protection with compensating membrane Mounting option: screw bracket (for mounting panel thickness from 1 up to 15 mm) Display: LED, 4-digit from -1999 ... 9999 Accuracy of reading: +/- 0.2 % of span +/- 1 digit Input: multi-function input (input configuration setable) setable input configurations: Pt100, thermocouples type K/J/R/S/B/E/T/N/PL-II/C, 0/4...20 mA, 0...1/5/10 V, 1...5 V Power supply: AC/DC 24 V Output configuration: transmitter supply (DC 24 V max. 30 mA) and 2 alarm outputs Special design features: without Terminal cover: fixed with screws (protection against contact)

© 2023 - WIKA Instruments s.a.r.l.