DATASHEET - XV-313-70-C00-A00-1C

Rear mounting control panel; 24 V DC; 7 Inches PCT-Display; 1024x600 pixels; 2xEthernet; 1xRS232; 1xRS485; 1xCAN; 1xSD slot

Part no. **XV-313-70-C00-A00-1C**
191059

Product name	Eaton XV-313 Touch panel
Part no.	XV-313-70-C00-A00-1C
EAN	7640130099074
Product Length/Depth	209 millimetre
Product height	50 millimetre
Product width	151 millimetre
Product weight	0.8 kilogram
Certifications	IEC/EN 61131-2 CE UL 61010-2-201 UL EN 50178 UL File No.: E205091 CUL EMC according to 2014/30/EU Certified by UL for use in Canada DNV GL
Product Tradename	XV-313
Product Type	Touch panel
Product Sub Type	None
Catalog Notes	11.9 W for basic device + 2.5 W for USB module Heat dissipation with power consumption for 24 V License certificates for onboard interfaces not required Optionally with SD card -> article no. 181638 PLC license inclusive
Enclosure material	Insulated material
Features	Ethernet interface Portrait format USB device RS232 Target and web visualization Operating System Windows Embedded Compact 7 pro Fanless CPU and system cooling, natural convection-based passive cooling RS485 USB Host CAN Slot for SD card Integrated Runtime visualization software license
Fitted with:	1 x RS485 (built-in interface) Printer output 1 x USB host 2.0 (built-in interface) 1 x RS232 (built-in interface) Message indication Recipes SW interfaces Color display Message system (incl. buffer and confirmation) 1 x USB device (built-in interface) 1 x CANopen®/easyNet (built-in interfaces) 2 x Ethernet 10/100 Mbps (built-in interface)
Functions	Process value representation (output) possible Additional software components, loadable Process default value (input) possible
Battery runtime	Back-up of real-time clock: BR 2330, non-replaceable (soldered)
Degree of protection	IP20, rear (according to EN 60529-1) NEMA 12 NEMA 4X
Degree of protection (front side)	IP65 NEMA 12
Fuse type	Built-in fuse (not accessible)
Lifespan	50,000 h (Service life of back-lighting)
Model	Plastic enclosure and glass panel in aluminum mounting frame

Mounting method	Rear mounting Flush mounting - Clearance: Width x Height x Depth ≥ 30 mm (1.18") Flush mounting - Inclination from vertical: ±45° (if using natural convection)
Potential isolation	Power supply: no
Protection against polarity reversal	Yes, for supply voltage (Siemens MPI optional)
Product category	HMI-PLC (integrated SPS function)
RoHs conformity	Yes
Software	XSOFT-CODESYS-2, PLC-Programming software, Engineering XSOFT-CODESYS-3, PLC-Programming software, Engineering XSOFT-CODESYS, Visualisation software, Engineering GALILEO, Visualisation software, Engineering
Type	Control panel with PLC and 2nd Ethernet port
Voltage type	DC
Shock resistance	15 g, 11 ms, Mechanical
Vibration resistance	5 - 9 Hz, ± 3.5 mm 60 - 150 Hz, ± 2 g 9 - 60 Hz, ± 0.15 mm
Air pressure	795 - 1080 hPa (operation)
Ambient operating temperature - min	0 °C
Ambient operating temperature - max	50 °C
Ambient storage temperature - min	-20 °C
Ambient storage temperature - max	60 °C
Climatic proofing	Dry heat to IEC 60068-2-2 Damp heat, constant, to IEC 60068-2-3 Cold to EN 60068-2-1
Environmental conditions	Condensation: Non-condensing
Operating temperature - min	0 °C
Operating temperature - max	50 °C
Relative humidity	10 - 95 % (non-condensing)
Emitted interference	According to IEC/EN 61000-6-4
Interference immunity	According to EN 61000-6-2
Voltage dips	≤ 10 ms from rated voltage (24 V DC) 5 ms from undervoltage (19.2 V DC)
Permissible voltage	18.0 - 31.2 V DC, absolute with ripple 18 - 31.2 V DC, battery powered (rated operating voltage -25 %/+30 %) 35 V DC (for a duration of < 100 ms) 19.2 - 30 V DC, effective (rated operating voltage -20 %/+25 %)
Power consumption	Max. 14.4 W 14 W typ.
Rated operational voltage	24 V DC (power-supply - safety extra low voltage)
Supply voltage at AC, 50 Hz - min	0 V AC
Supply voltage at AC, 50 Hz - max	0 V AC
Supply voltage at DC - min	19.2 V DC
Supply voltage at DC - max	30 V DC
Interfaces	10/100 Mbps Ethernet connection RS232 (not galvanically isolated, 9-pin SUB-D plug, UNC) CAN (not galvanically isolated, 9-pin SUB-D plug, UNC) USB 2.0 device (not galvanically isolated) RS485 (not galvanically isolated, 9-pin SUB-D plug, UNC) USB 2.0 host (not galvanically isolated)
Number of slots	1 (for SD-Card)
Protocol	TCP/IP CAN EtherNet/IP MODBUS
Display contrast ratio	500:1
Display lighting	Dimmable via software LED
Display size	153.6 x 90.0 mm

			16:9
Display type			Color display, TFT, anti-glare Anti-glare tempered glass without bezel TFT
Luminance intensity			400 cd/m²
Number of colors of the display			16777216
Resolution			1024 x 600 px WSVGA
Screen size (diagonal)			7 in
Touch technology			Projected Capacitive Touch (PCT) Capacitive multitouch Multi-touch touch panel touch sensor
Backup time			10 years, typ. (time at zero voltage)
Memory			NVRAM: 128kByte Retain Flash: 1 GByte SLC DRAM: 512 MByte RAM SD card, Type: SDSC, SDHC (external memory)
Memory capacity			512,000 kByte
Operating system			Windows Embedded Compact 7 Pro
Processor			ARM Cortex-A9 800 MHz
Equipment heat dissipation, current-dependent Pvid			14.4 W
Heat dissipation capacity Pdiss			0 W
Heat dissipation per pole, current-dependent Pvid			0 W
Rated operational current for specified heat dissipation (In)			0 A
Static heat dissipation, non-current-dependent Pvs			14.4 W
10.2.2 Corrosion resistance			Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects			Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation			Please enquire
10.2.5 Lifting			Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact			Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of assemblies			Meets the product standard's requirements.
10.4 Clearances and creepage distances			Meets the product standard's requirements.
10.5 Protection against electric shock			Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 8.0

Programmable logic controllers PLC (EG000024) / Graphic panel (EC001412)		
Electric engineering, automation, process control engineering / Display and control component / Panel (HMI) / Graphic panel (HMI) (ecl@ss10.0.1-27-33-02-01 [AFX016003])		
Supply voltage AC 50 Hz	V	0 - 0
Supply voltage AC 60 Hz	V	0 - 0
Supply voltage DC	V	19.2 - 30
Voltage type of supply voltage		DC
Number of HW-interfaces industrial Ethernet		2

Number of interfaces PROFINET		0
Number of HW-interfaces RS-232		1
Number of HW-interfaces RS-422		0
Number of HW-interfaces RS-485		1
Number of HW-interfaces serial TTY		0
Number of HW-interfaces USB		2
Number of HW-interfaces parallel		0
Number of HW-interfaces Wireless		0
Number of HW-interfaces other		1
With SW interfaces		Yes
Supporting protocol for TCP/IP		Yes
Supporting protocol for PROFIBUS		No
Supporting protocol for CAN		Yes
Supporting protocol for INTERBUS		No
Supporting protocol for ASI		No
Supporting protocol for KNX		No
Supporting protocol for Modbus		Yes
Supporting protocol for Data-Highway		No
Supporting protocol for DeviceNet		No
Supporting protocol for SUCONET		No
Supporting protocol for LON		No
Supporting protocol for PROFINET IO		No
Supporting protocol for PROFINET CBA		No
Supporting protocol for SERCOS		No
Supporting protocol for Foundation Fieldbus		No
Supporting protocol for EtherNet/IP		Yes
Supporting protocol for AS-Interface Safety at Work		No
Supporting protocol for DeviceNet Safety		No
Supporting protocol for INTERBUS-Safety		No
Supporting protocol for PROFIsafe		No
Supporting protocol for SafetyBUS p		No
Supporting protocol for other bus systems		No
Radio standard Bluetooth		No
Radio standard Wi-Fi 802.11		No
Radio standard GPRS		No
Radio standard GSM		No
Radio standard UMTS		No
IO link master		No
Type of display		TFT
With colour display		Yes
Number of colours of the display		16,777,216
Number of grey-scales/blue-scales of display		0
Screen diagonal	inch	7
Number of pixels, horizontal		1,024
Number of pixels, vertical		600
Useful project memory/user memory	kByte	512,000
With numeric keyboard		No
With alpha numeric keyboard		No
Number of function buttons, programmable		0
Number of buttons with LED		0
Number of system buttons		1
Touch technology		Capacitive multitouch
With message indication		Yes
With message system (incl. buffer and confirmation)		Yes
Process value representation (output) possible		Yes

Process default value (input) possible			Yes
With recipes			Yes
Number of password levels			200
With printer output			Yes
Number of online languages			100
Additional software components, loadable			Yes
Degree of protection (IP), front side			IP65
Degree of protection (NEMA), front side			12
Operating temperature		°C	0 - 50
Rail mounting possible			No
Wall mounting/direct mounting			No
Suitable for safety functions			No
Width of the front		mm	181.5
Height of the front		mm	125.6
Built-in depth		mm	50.1

© 04/2023 by Eaton Industries GmbH