Date: 11/04/2023

TR33, PT100-3w, cl.A, G1/4 fixed, 25 mm x 3 mm

TR33 Miniature resistance thermometer, thread-mounted

Item number: 48703855

Quantity: 1 pcs.

Order code: TR33-Z-P3-ZMZZZZ-1130025-ZZZ-7ZZ-BZZ R33 0036ZPZZZZWIKA0Z
CERT22-EG32-AA- - - - - - - - - - - TE-CT3

Overview: TR33, PT100-3w, cl.A, G1/4 fixed, 25 mm x 3 mm

Output signal: PT100-3w, cl.A
Electrical connection: Circular connector, M12x1

Process connection: Fixed threaded hex bushing G1/4 B
Process temperature: -30 ... +150°C
Sensor diameter ød: 3 mm
Insertion length A: 25 mm
Permissible ambient temperature: -50 ... +85 °C (-58 ... +185 °F)
Pin assignment: Standard pin connection Pt-Sensors (see datasheet)

Specifications according to data sheet: TE 60.33

Test certificate acc. to EN 10204 2.2
Certificate Language: English and German
Electrical Thermometer
Formal certificate: Manufactured according to state-of-the-art

Details: TR33 Miniature resistance thermometer, thread-mounted
Specifications according to data sheet: TE 60.33
Electrical connection: Circular connector, M12x1
Output signal: Pt100 Class A (IEC 60751), 3-wire
Process temperature: -30 ... +150°C
Process connection: Fixed threaded hex bushing G1/4 B
Sensor diameter ød: 3 mm
Insertion length A: 25 mm
Permissible ambient temperature: -50 ... +85 °C (-58 ... +185 °F)
Pin assignment: Standard pin connection Pt-Sensors (see datasheet)
Test certificate acc. to EN 10204 2.2
Certificate Language: English and German
Electrical Thermometer
Formal certificate: Manufactured according to state-of-the-art

© 2023 - WIKA Instruments s.a.r.l.