PRODUCT-DETAILS

E4.2V 4000 Ekip Hi-Touch LSIG 3p F HR

E4.2V 4000 Ekip Hi-Touch LSIG 3p F HR



General Information

Extended Product Type	E4.2V 4000 Ekip Hi-Touch LSIG 3p F HR
Product ID	1SDA071229R1
EAN	8015644750794
Catalog Description	E4.2V 4000 Ekip Hi-Touch LSIG 3p F HR
Long Description	C.BREAKER SACE EMAX2 E4.2V 4000 FIXED THREE-POLE WITH TERMINALS REAR HORIZONTAL AND SOLID-STATE RELEASE IN AC EKIP/HI-TOUCH-LSIG R 4000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

ABB EcoSolutions

ABB EcoSolutions	Yes
Environmental Product Declaration - EPD	9AKK108468A1904 9AKK108468A1910

Material Compliance

REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424

© 2024 ABB. All rights reserved.

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326
SCIP	b192bb07-b5f3-4f11-af38-7141ee85eec4 Italy (IT)
Simplified SCIP	1f147c33-3f28-436f-bc08-2b375b66cf98 Sweden (SE) 05a8455e-8079-41d1-a46a-1e6757bc9f61 Estonia (EE) 0ae63d78-8bcb-42de-8a5d-136d4987e63c Belgium (BE) d7ff7229-7658-4f8c-90a7-ac511daeef38 Spain (ES) 6df12662-9d4b-40bc-a3b5-b5099c640c1f Sweden (SE) 64049ae5-6e8a-4f48-bd3b-9e84370df94c France (FR) 437001c7-9d27-44fe-95e1-5b4b7ab28238 Poland (PL) 02bb39ff-a634-4fba-8e42-e09ae1227f96 Hungary (HU) 42b8c629-e3db-4cdc-ac3b-0d72abe74997 Bulgaria (BG) 212f5ba8-48e7-4f0d-a088-b26ac9e8099d Czech Republic (CZ) 5bf6128b-ee75-4f0f-9d62-a6fc9848bfd5 Netherlands (NL) 05a8455e-8079-41d1-a46a-1e6757bc9f61 Estonia (EE) 1fa3cc9b-426c-4999-93c8-6548d2c2bf7b Hungary (HU) bc17557f-c183-459d-9479-ec8458edbc4b Poland (PL) d7ff7229-7658-4f8c-90a7-ac511daeef38 Spain (ES) 8373101f-158e-4e30-8871-c94b03386cc5 France (FR) 1fa3cc9b-426c-4999-93c8-6548d2c2bf7b Hungary (HU) e5e303ee-1a58-46da-a437-551fe5fa400b Germany (DE) 614d191c-3cd3-474b-b472-970a0cac04ae Germany (DE) c4a404e1-5acb-4810-bc98-e63abda79243 Norway (NO) c41201fd-53c0-485c-a152-67cba3c7c78d Germany (DE) e9523c38-6d2e-4877-a993-2cf9a48b3d64 Belgium (BE) 0ae63d78-8bcb-42de-8a5d-136d4987e63c Belgium (BE) fa40c56b-358c-4fae-89a9-0a9f68cee3bc Denmark (DK) 42b8c629-e3db-4cdc-ac3b-0d72abe74997 Bulgaria (BG) e9523c38-6d2e-4877-a993-2cf9a48b3d64 Belgium (BE) bdf51999-a35a-4e9b-82dd-c3517344d6c4 Germany (DE) 5367f5c0-817d-430b-82da-9e87efa0c2e5 Finland (FI) c41201fd-53c0-485c-a152-67cba3c7c78d Germany (DE) 1f147c33-3f28-436f-bc08-2b375b66cf98 Sweden (SE) 080a1a99-d781-4849-890a-bbdf7957422a Germany (DE) 437001c7-9d27-44fe-95e1-5b4b7ab28238 Poland (PL) 8373101f-158e-4e30-8871-c94b03386cc5 France (FR) 212f5ba8-48e7-4f0d-a088-b26ac9e8099d Czech Republic (CZ) e5e303ee-1a58-46da-a437-551fe5fa400b Germany (DE) 4932bb80-514a-48dd-9feb-892210f3e20f Croatia (HR) 6df12662-9d4b-40bc-a3b5-b5099c640c1f Sweden (SE) 5bf6128b-ee75-4f0f-9d62-a6fc9848bfd5 Netherlands (NL) 02bb39ff-a634-4fba-8e42-e09ae1227f96 Hungary (HU) 5408363a-85bd-457c-a04d-4b4004ba32d5 Portugal (PT) 614d191c-3cd3-474b-b472-970a0cac04ae Germany (DE) 77044ac6-a346-4e09-b96f-58b9a8aedecd Poland (PL) fa40c56b-358c-4fae-89a9-0a9f68cee3bc Denmark (DK) c4a404e1-5acb-4810-bc98-e63abda79243 Norway (NO) 4932bb80-514a-48dd-9feb-892210f3e20f Croatia (HR) 5367f5c0-817d-430b-82da-9e87efa0c2e5 Finland (FI) 64ad2c35-aa15-4890-b28c-c92fac96adec Greece (GR) bdf51999-a35a-4e9b-82dd-c3517344d6c4 Germany (DE) 64049ae5-6e8a-4f48-bd3b-9e84370df94c France (FR) 5408363a-85bd-457c-a04d-4b4004ba32d5 Portugal (PT) 64ad2c35-aa15-4890-b28c-c92fac96adec Greece (GR) 77044ac6-a346-4e09-b96f-58b9a8aedecd Poland (PL) 080a1a99-d781-4849-890a-bbdf7957422a Germany (DE) bc17557f-c183-459d-9479-ec8458edbc4b Poland (PL)

Environmental

Environmental Information	9AKK108467A6707

© 2024 ABB. All rights reserved.

Ordering

Order Code US and Canada	Z4VWERBK200A000000XX
EAN	8015644750794
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	384 mm
Product Net Height	371 mm
Product Net Depth / Length	270 mm
Product Net Weight	56 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	515 mm
Package Level 1 Height	610 mm
Package Level 1 Depth / Length	615 mm
Package Level 1 Gross Weight	63 kg
Package Level 1 EAN	8015644750794

Additional Information

Product Main Type	SACE Emax 2
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Version	F
CAD Dimensional Drawing	1SDH001252R0171

Technical

Current Type	AC
Electrical Durability	Ue =< 440 V 5000 cycle Ue = 500 ... 690 V 4000 cycle 20 cycles per hour
Mechanical Durability	15000 cycle 60 cycles per hour
Number of Poles	3P
Power Loss	465 W
Rated Current (I_n)	4000 A
Rated Impulse Withstand Voltage (U_{imp})	acc. to IEC 60947-2 12 kV
Rated Insulation Voltage (U_i)	AC 1000 V
Rated Operational Voltage	690 V AC
Rated Service Short-	(220 V AC) 150 kA

© 2024 ABB. All rights reserved.

Circuit Breaking Capacity (I_{cs})	(230 V AC) 150 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 150 kA (500 V AC) 100 kA (660 V AC) 100 kA (690 V AC) 100 kA
Rated Service Short-Circuit Breaking Capacity, in % of Icu (I_{cs})	100 %
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 1 s 100 kA for 3 s 75 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 150 kA (500 V AC) 100 kA (525 V AC) 100 kA (690 V AC) 100 kA
Rated Uninterrupted Current (I_u)	4000 A
Rated Voltage (U_r)	690 V
Recommended Screw Driver	Main Circuit M12
Release	Ekip Hi-Touch LSIG
Release Type	EL
Short-Circuit Performance Level	V
Standards	IEC
Sub-type	E4.2
Suitable for IT Networks	Yes, 690V
Terminal Connection Type	Rear flat Horizontal
Terminal Type	Bolt
Tightening Torque	70 N·m

Certificates and Declarations

ATEX Certificate	No certification needed
CSA Certificate	No certification needed
CSA Certificate (Intrinsic Safe)	No certification needed
Data Sheet, Technical Information	1SDC200023D0209
Declaration of Conformity - CE	9AKK106713A5545
UL Certificate	No certification needed
VDE Certificate	No certification needed
Mechanical Drawings	1SDH001001R0100
Wiring Diagram	1SDM000091R0001
Instructions and Manuals	1SDH001000R0002
Instructions and Manuals (Part 2)	1SDH001316R1002

Classifications

ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation

© 2024 ABB. All rights reserved.

	protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA Granular Category Code (IGCC)	4926 >> Air circuit breakers
Object Classification Code	Q
UNSPSC	39121615
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2



© 2024 ABB. All rights reserved.