PRODUCT-DETAILS

SS32/25M

32MM GS CONDUIT 25M - MET



General Information

Extended Product Type:	SS32/25M
Product ID:	7TCA296120R0032
EAN:	5020963005947
Catalog Description:	32MM GS CONDUIT 25M - MET
Long Description:	Inherent Low Fire Hazard Conduit, 1 Inch, Nominal Conduit Size 32mm, Outside Diameter 32.0mm, Inside Diameter 28.1mm, Static Bend Radius 60mm, Reel Length 25 Meters, 316 Stainless Steel, Corrosion Resistant
Display Name:	SS32/25M

Additional Information

Product Main Type:	Adaptaflex Flexible Cable Protection
Application:	Indoors / Outdoors - Corrosive Environments

Ordering

EAN:	5020963005947

© 2026 ABB. All rights reserved.

UPC:	786210249575

Dimensions

Outside Diameter:	32.0 mm

Technical

Number of Batteries:	0
Material:	Stainless Steel

Environmental

WEEE Category:	Product Not in WEEE Scope
RoHS Information:	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Container Information

Package Level 1 Units:	1 piece
Package Level 1 EAN:	5020963005947
Package Level 1 Height:	12 in 305 mm
Package Level 1 Depth / Length:	16 in 406 mm
Package Level 1 Width:	16 in 406 mm

Certificates and Declarations

Declaration of Conformity - CE:	9AKK107492A9618
RoHS Declaration:	9AKK107992A8994
REACH Declaration:	9AKK107992A8994

External Classifications and Standards

ETIM 8:	EC001179 - Protective metallic hose
ETIM 9:	EC001179 - Protective metallic hose
UNSPSC:	39131706

Categories

© 2026 ABB. All rights reserved.

Products > Low Voltage Products and Systems > Installation Products > Cable Protection, Explosion Proof and Lighting > Flexible Cable Protection Systems



© 2026 ABB. All rights reserved.