INVINCIBLE® FACESHIELD

YELLOW CHIN & BROWGUARD - CLEAR ACETATE BOUND VISOR - 8"/20CM

PRODUCT CODE: AFB011-330-200

OFFERS PROTECTION AGAINST LOW ENERGY HIGH SPEED PARTICLES AT 45M/S (101MPH) & LIQUID DROPLETS

TECHNICAL SPECIFICATION

EYE & FACE PROTECTION

INSTRUCTIONS FOR USE

- Before use, the browguard should be fitted to an Invincible Visor and Chinguard (where applicable)
- In use, ensure that the Faceshield fits comfortably and securely on the head
- Ensure that the visor is in place before entering the hazard area



MATERIALS

- Browguard: Polycarbonate
- Chinguard: Polycarbonate
- Head Harness: Nylon with Steel Fittings
- Visor: Acetate, Aluminium Binding
- Nickel Plated Brass Press Studs

DIMENSIONS OF OUTER PACKAGING

- Quantity: 20
- Height: 760mm
- Width: 440mm
- Length: 590mm
- Weight: 9.2kg (Approx.)

DIMENSIONS OF FACESHIELD

- Height: 175mm
- Width: 263mm
- Length: 355mm
- Weight: 414g (Approx.)
- Size: 52 - 64cm

CLEANING & MAINTENANCE

- The browguard may be cleaned with soap and warm water and dried with a soft cloth
- Do not clean with chemical or abrasive cleaners
- The eye shield should be stored out of direct sunlight, away from chemicals and not exposed to extremes of temperature

CONFORMITY

- Conforms to EN166
- EC Certificate Number 682750, issued by BSi Product Certification
- Markings: EN 166 1.F.3

FACESHIELD FEATURES & PERFORMANCE

- Offers protection against low energy high speed particles at 45m/s (101mph), liquid droplets and molten metal
- The optical qualities of the visor comply with the requirements of optical class 1 (highest)

LIMITATIONS OF USE

- Protection will only be offered if the faceshield is fitted correctly
- If the faceshield becomes scratched or damaged they should be replaced
- Do not apply paint, solvents, adhesives or self-adhesive labels, except in accordance with instructions from the manufacturer
- The Acetate and Polycarbonate visors are not suitable for use with all chemicals - if you are unsure contact your supplier or JSP for advice

DISCLAIMER: Information presented within this technical specification was correct on date of issue. Information may be subject to change without notice as part of ongoing product improvement and development. To confirm any specific piece of information shown is current please email technical@jsp.co.uk.