Date: 11/04/2023

SC15.30.060 0 ... 120°C CL.2

Mechanical Temperature Regulator, Safety Temperature Limiter,

Item number: 6038489

Quantity: 1 pcs.

Order code: SC15-ZZ30060AA00CLL4AAZZZZZZZZZA1000Z95M0850035L1Z5
ZZZZZZZZ1ZZZZZZZB2ZZ

Overview:
SC15.30.060 0 ... 120°C CL.2
standard, plastic case
Panel mounting with clamp, front ring chrome plated,
1 adjustable changeover switch,
adjusting knob with key
5 A non-inductive at max. 250VAC 50/60Hz
terminal block
Capillary [FL]: 10.00 m Copper plastic covered,
Connection design: SF95 M10x1
Insertion length [L1] o. [U1]: 35 x 8,5 mm brass
Dial background: White *WIKA*

Details:
Mechanical Temperature Regulator, Safety Temperature Limiter,
Safety Temperature Alerter
Model: SC15, Combistat
Nominal size [NG, d1]: 60 mm
Unit: °C
Scale range: 0 °C ... 120 °C
Case material: Plastic, black;
Mounting option: Panel mounting with clamp
Bezel ring: bezel ring, chrome plated
Ingress protection: IP53 (front), IP00 (rear)
Contact type: 1 adjustable change-over switch
Switch rating: 5 A non-inductive at max. 250VAC 40-60Hz
Cable connection: terminal block
SWITCH ADJUSTMENT: adjusting knob with key
Capillary length
Capillary material: Copper plastic covered
Connection design: spring and connection M10x1 (SF95)
Stem diameter [d5]: 8.5 mm
Insertion length [L1]: Length is calculated automatically
Stem material: Copper alloy
Process connection [E]: M10x1
Connection material: Copper alloy
Accuracy class: class 2 per EN 13190
dial background: White
Manufacturer logo: *WIKA*
Data sheet: TV28.02

© 2023 - WIKA Instruments s.a.r.l.

Tension thermometer - Indicating temperature controller SC15
Specifications according to data sheet: TV 28.02
Model: SC15 - combistat
Design: standard, plastic case
Nominal size [NG, d1]: 60 mm
Mounting option: Panel mounting with clamp,
Front ring: front ring chrome plated
Unit: °C
Scale range: 0 ... 120°C
Contact type: 1 adjustable changeover switch,
Contact adjustment: adjusting knob with key
Switch rating: 5 A non-inductive at max. 250VAC 40-60Hz
Cable connection: terminal block
Capillary material: Copper plastic covered,
Capillary [ML]: 10,00
Connection design: SF95 - Screw M10x1 with print spring,
Probe material: brass
Probe diameter [d5] o. [F1]: 8,5 mm
Insertion length [L1] o. [U1]: 35
Process connection [E o. d6]: Male thread M10x1
Manufacturer logo: *WIKA*
Accuracy class: class 2 per EN 13190
Dial background: White
Tension thermometer - Indicating temperature controller SC15
Specifications according to data sheet: TV 28.02
Model: SC15 - combistat
Design: standard, plastic case
Nominal size [NG, d1]: 60 mm
Mounting option: Panel mounting with clamp,
Front ring: front ring chrome plated,
Unit: °C
Scale range: 0 ... 120°C
Contact type: 1 adjustable changeover switch,
Contact adjustment: adjusting knob with key
Switch rating: 5 A non-inductive at max. 250VAC 50/60Hz
Cable connection: terminal block
Capillary material: Copper plastic covered,
Capillary [FL]: 10.00
Connection design: SF95 - Screw M10x1 with print spring,
Probe material: brass
Probe diameter [d5] o. [F1]: 8,5 mm
Insertion length [L1] o. [U1]: 35
Process connection [d6 o. E]: Male thread M10x1
Manufacturer logo: *WIKA*
Accuracy class: class 2 per EN 13190
Dial background: White

© 2023 - WIKA Instruments s.a.r.l.