Date: 11/04/2023

F73.100/4, -80...+60°C, L1=395x6mm,

Gas actuated thermometer, stainless steel series

Item number: 48768132

Quantity: 1 pcs.

Order code: F73.100-CHA-4ND-B0395-S02-4-Z-HZZ-AHAZZZ G7 FZZZEVZZIWS-AZ1ZZZZZ2ZZZZ

Overview:
F73.100/4, -80...+60°C, L1=395x6mm,
1/2 NPT radial bottom
Surface mounting bracket, die cast aluminium
stainless steel armoured capillary
Capillary length: 2 m
laminated safety glass
Explosion protection: ATEX Ex h Gas Zone 1 / Dust Zone 21 (II 2G Ex h IIC T6 ... T1 Gb X / II 2D Ex h IIIC T85 °C … T450 °C Db X)
class 1 per EN 13190
WIKA
with Serial number

Details:
Gas actuated thermometer, stainless steel series
Specifications according to data sheet: TM 73.01
Case: stainless steel
Stem material: stainless steel
Model: F73.100, nominal size 100, with capillary
Unit: °C
Scale range: -80 °C ... +60 °C
Connection design: 4, compression fitting, sliding on stem
Process connection: 1/2 NPT
Stem diameter: 6 mm
Insertion length L1: 395
Capillary: stainless steel armoured capillary
Capillary length: 2 m
Design of case mounting: Surface mounting bracket, die cast aluminium
Explosion protection: ATEX
Ignition protection type: Ex h
Zone: Gas Zone 1 / Dust Zone 21 (II 2G Ex h IIC T6 ... T1 Gb X / II 2D Ex h IIIC T85 °C … T450 °C Db X)
Accuracy class: class 1 per EN 13190
Ingress protection: IP 65
Window: laminated safety glass
Case: Stainless steel
Connector location: radial bottom
Manufacturer logo: *WIKA*
Permissible ambient temperature: -40 … +60 °C
with Serial number

© 2023 - WIKA Instruments s.a.r.l.