Date: 11/04/2023

TSD-30 ; -20 ... +120 °C (enclosed compression fitting required); two switching output (PNP) + 4...20 mA

Electronic Temperature Switch with Display Model TSD-30

Item number:	48756152
Quantity:	1 pcs.
Order code:	TSD-30-Q-CB-M0250-K9C-M5-WW-ZZ W1011TS3-C2ZZZ-S3R-GSFK
Overview:	TSD-30 ; -20 ... +120 °C (enclosed compression fitting required); two switching output (PNP) + 4...20 mA @ 15...35 V DC; Probe length: 250 mm; compression fitting, G 1/2 A DIN 3852-A Sealing: copper 5-pin locking plug M12 x 1 U+=1, U-=3, S+=5, SP1=4, SP2=2 Approvals: cULus Specifications according to data sheet: TE 67.03
Details:	Electronic Temperature Switch with Display Model TSD-30 Specifications according to data sheet: TE 67.03 Output signal: two switching output (PNP) + 4...20 mA Temperature range: -20 ... +120 °C (enclosed compression fitting required) Probe length unit: mm Process connection: compression fitting, G 1/2 A DIN 3852-A Sealing: copper Electrical connection: 5-pin locking plug M12 x 1 Approvals: cULus Pin assignment: U+=1, U-=3, S+=5, SP1=4, SP2=2 Power supply: 15...35 V DC Probe length: 250 mm

© 2023 - WIKA Instruments s.a.r.l.