Date: 11/04/2023

ARV2"-VU-L1,200/12-V44A

ARV2"-VU-L1,200/12-V44A

Item number:	48771038
Quantity:	1 pcs.
Order code:	FLS-CBMZZ000510900DA9ZZGFZZ1150UZZZZZZZZZZZZZZZZZZ KBRVJA12001NZZZZ
Overview:	ARV2"-VU-L1,200/12-V44A Float Switch Type FLS-SA Material: Stainless steel 316Ti (EN 1.4571) Pressure: 0.5 bar Temperature range: -10°C up to 80°C Fluid density: 900 kg/m³ Housing: Aluminium Ingress protection: IP66/68 Electrical connection: M16 x 1.5 mm with cable gland Process connection: Mounting thread downwards 2"BSP Switch function 1: Change-over (SPDT) 1150 mm Switch rating: max. AC 230V; 40VA; 1A / DC 230V; 20W; 0.5A Float: Stainless steel 316Ti V44A; Float outer diameter: 44 mm Number of floats: 1 pc Guide tube: OD 12 mm Insertion length (L): 1200 mm Float stop: Float collar Float fits through the connection nozzle Weight: 1.5 kg
Details:	ARV2"-VU-L1,200/12-V44A Float Switch Type FLS-SA Material: Stainless steel 316Ti (EN 1.4571) Pressure: 0.5 bar Temperature range: -10°C up to 80°C Fluid density: 900 kg/m³ Housing: Aluminium Ingress protection: IP66/68 Electrical connection: M16 x 1.5 mm with cable gland Process connection: Mounting thread downwards 2"BSP Switch function 1: Change-over (SPDT) 1150 mm Switch rating: max. AC 230V; 40VA; 1A / DC 230V; 20W; 0.5A Float: Stainless steel 316Ti V44A; Float outer diameter: 44 mm Number of floats: 1 pc Guide tube: OD 12 mm Insertion length (L): 1200 mm Float stop: Float collar Float fits through the connection nozzle Weight: 1.5 kg

© 2023 - WIKA Instruments s.a.r.l.