DATASHEET - CSAS6A6CY2205

Connection cable; 6p; AC; coupling M12 flat; open end; L=5m

Part no. **CSAS6A6CY2205**
177307

Product name	Eaton Moeller® series CSAS Accessory Connection cable
Part no.	CSAS6A6CY2205
EAN	4015081717606
Product Length/Depth	250 millimetre
Product height	25 millimetre
Product width	175 millimetre
Product weight	0.216 kilogram
Compliances	CE
Product Tradename	CSAS
Product Type	Accessory
Product Sub Type	Connection cable
Ambient operating temperature - max	70 °C
Ambient operating temperature - min	-25 °C
Cable length	5 m
Cable length [7EF000536]	m
Cable sheath material	Other
Cable type	Multi-core Cable end, open, Output side Coupling, straight, Input side
Color cable sheath	Yellow
Contact body material	Other
Contact surface material	Other
Continuity resistor	0 mΩ
Continuity resistor [7EF003992]	MO
Degree of protection	Other
Electrical connection type (box-sided)	Other
Electrical connection type (field-sided)	M12
Nominal current	0 A
Number Of Poles	Six-pole
Permitted cable outer temperature after assembling without vibration [7EF001686]	°C
Permitted cable outer temperature during assembling/handling [7EF001685]	°C
Permitted temperature of outer cable (assembled) without vibration - max	70 °C
Permitted temperature of outer cable (assembled) without vibration - min	40 °C
Permitted temperature of outer cable (assembling/handling) - max	70 °C
Permitted temperature of outer cable (assembling/handling) - min	40 °C
Plug-in contact type (field-sided)	Female (bus)
Positioning cable feed (box-sided)	Other
Positioning cable feed (field-sided)	Straight
Product category	Accessories
Rated current In [7EF008250]	A
Rated operational voltage (Ue) - max	0 V
Rated voltage [7EF000228]	V
Voltage type	DC

Technical data ETIM 8.0

Sensors (EG000026) / Sensor-actuator patch cord (EC001855)

Electric engineering, automation, process control engineering / Cable, wire / Ready-made data cable / Assembled sensor/actuator adapter, with cable (ecl@ss10.0.1-27-06-03-13 [AFR625003])

Number of poles		6
Type of electrical connection, field-sided		M12
Type of plug-in contact, field sided		Female (bus)
Positioning cable feed, field-sided		Straight
Type of electrical connection, box-sided		Other
Type of plug-in contact, box-sided		
Positioning cable feed, box-sided		Other
Cable length	m	5
Material of cable sheath		Other
Halogen free		No
Colour cable sheath		Yellow
With LED indication		No
Screened		No
Cable type		Multi-core
Vulcanize		No
Material contact body		Other
Material of contact surface		Other
Permitted cable outer temperature after assembling without vibration	°C	40 - 70
Permitted cable outer temperature during assembling/handling	°C	40 - 70
Rated current In	A	0
Rated voltage	V	0
Continuity resistor	mOhm	0
Degree of protection (IP)		Other

© 04/2023 by Eaton Industries GmbH