DATASHEET - IZMX-AS22-40-1

Signalling switch ON-OFF, 2W

Part no. IZMX-AS22-40-1
184115

EL Number (Norway) 4398478

General specifications

Product name			Eaton Moeller series IZMX/INX auxiliary contact block
Part no.			IZMX-AS22-40-1
EAN			4015081783182
Product Length/Depth			100 millimetre
Product height			100 millimetre
Product width			100 millimetre
Product weight			0.068 kilogram
Compliances			RoHS conform
Product Tradename			IZMX/INX
Product Type			Accessories
Product Sub Type			Auxiliary contact block

Delivery program

Type			Accessory
Model			Integrable
Special features			Mounting kit with 2 additional changeover contacts with cable lengths for IZMX40. The basic device already contains two changeover contacts. The retrofit kit includes the required SEC control cable terminals. Retrofit kit for IZMX40 circuit-breakers 2 changeover contacts
Used with			INX40... IZMX40...

Technical Data - Electrical

Rated operational current (Ie) at AC-15, 220 V, 230 V, 240 V			10 A
Rated breaking capacity (inductive load)			0.5 A (125 V DC) 0.25 A (250 V DC) 10 A (250 V AC)
Electric connection type			Flat plug-in connection

Technical Data - Mechanical

Mounting Method			Other
Number of contacts (change-over contacts)			2
Number of contacts (normally closed contacts)			0
Number of contacts (normally open contacts)			0
Number of switches (fault signal)			0
Lamp holder			None

Design verification as per IEC/EN 61439 - technical data

Ambient operating temperature - min			-25 °C
Ambient operating temperature - max			70 °C

Additional information

Accessory/spare part type			Auxiliary contact

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Auxiliary contact block (EC000041)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Auxiliary switch block (ecl@ss13-27-37-13-02 [AKN342018])

Number of contacts as change-over contact			2
Number of contacts as normally open contact			0
Number of contacts as normally closed contact			0
Number of fault-signal switches			0
Rated operation current Ie at AC-15, 230 V		A	10

Type of electric connection			Flat plug-in connection
Model			Integrable
Mounting method			Other
Lamp holder			None

© 04/2023 by Eaton Industries GmbH