Date: 22/01/2024

OLS-C05, G 1/2", Opened in media (SPST n.c.), circular connector M12x1, 4-pin

OLS-C05, G 1/2", Opened in media (SPST n.c.), circular connector M12x1, 4-pin

Item number:	14241092	
Quantity:	1 pcs.	
Order code:	OLS-C05-G1Z-HNCM4-ZZZZZ-ZZZ	W101OLS5Z1LH
Overview:	OLS-C05, G 1/2", Opened in media (SPST n.c.), circular connector M12x1, 4-pin Optoelectronic level switch, High temperature version Model: OLS-C05 Process connection: G 1/2" Output Signal: one switching output (PNP) Switch function: Opened in media (SPST n.c.) Power supply: 12 - 32 V DC Electrical connection: circular connector M12x1, 4-pin pin assignment el. connection: 1=U+, 3=U-, 4=SP Operating pressure: max. 25 bar Permissible medium temperature: -40…170 °C Wetted parts: Stainless steel 1.4571, borosilicate glass, epoxide resin Specifications according to data sheet: LM 31.33	
Details:	OLS-C05, G 1/2", Opened in media (SPST n.c.), circular connector M12x1, 4-pin Optoelectronic level switch, High temperature version Model: OLS-C05 Process connection: G 1/2" Output Signal: one switching output (PNP) Switch function: Opened in media (SPST n.c.) Power supply: 12 - 32 V DC Electrical connection: circular connector M12x1, 4-pin pin assignment el. connection: 1=U+, 3=U-, 4=SP Operating pressure: max. 25 bar Permissible medium temperature: -40…170 °C Wetted parts: Stainless steel 1.4571, borosilicate glass, epoxide resin Specifications according to data sheet: LM 31.33	

© 2024 - WIKA Instruments s.a.r.l.